



Empack Spraytech Inc.
98 Walker Drive
Brampton, Ontario, L6T 4H6
Canada
905-792-6571

PRODUCT: Emzone G24 Tech Lube - 320g

CODE: 045024

SECTION 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identity..... Emzone G24 Tech Lube - 320g
Product Item Numbers..... 045024
Manufacturer..... Empack Spraytech Inc.
98 Walker Drive
Brampton
Ontario
Canada
L6T 4H6
905-792-6571
24 hour emergency telephone number..... CANUTEC: (613)-996-6666 collect.
Recommended Use..... Lubricates film offers long lasting protection with corrosion and rust inhibitors .
Consumer Commodity..... Yes.
Hazard Ratings:
HMIS..... Health: 2 Fire: 4 Reactivity: 0.
NFPA Rating..... Health: 2 Fire: 4 Reactivity: 0.

SECTION 02: HAZARDS IDENTIFICATION

Emergency Overview..... Danger. Flammable aerosol. Contents under pressure. May catch fire. Container may explode if heated. Do not puncture. Do not burn. May cause skin and eye irritation. May be harmful by inhalation. KEEP OUT OF REACH OF CHILDREN .
Potential Health Effects:
Eye Contact..... May cause irritation, redness and pain.
Skin Contact Can cause skin irritation. Skin inflammation is characterized by itching, reddening, or blistering.
Ingestion..... Aspiration hazard if swallowed. Can enter lungs and cause damage. Can cause gastrointestinal disturbances.
Inhalation..... Inhalation may cause respiratory tract irritation. Can cause Central Nervous System (CNS) depression; symptoms include nausea, headache, dizziness, unconsciousness .

SECTION 03: COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS	CAS #	WT. %
Aliphatic Hydrocarbons	Unidentified	60-100
Isobutane	75-28-5	15-40
Propane	74-98-6	3-7

SECTION 04: FIRST AID MEASURES

Eye Contact..... Check for and remove contact lenses. Immediately flush eyes with water for a minimum of 15 minutes keeping eyelids open. Consult a doctor if any irritation occurs. Get medical attention if irritation persists.
Skin Contact..... Immediately flush the contaminated skin with soap and water. If this chemical penetrates clothing, immediately remove the clothing and flush the skin with water. If irritation persists after washing, get medical attention .
Ingestion..... If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting.
Inhalation..... Move victim to fresh air. If breathing has stopped, give artificial respiration. If heartbeat absent, give external cardiac compression. Monitor breathing and pulse. If symptoms persist, call a physician.
Additional Information..... Note to the doctor; treat symptomatically.

SECTION 05: FIRE FIGHTING MEASURES

Flammability Class..... Flammable.
Extinguishing Media..... Carbon dioxide, dry chemicals, foam or water fog.
Sensitivity to Mechanical Impact..... Not expected to be sensitive.
Sensitivity to Static Discharge..... Can be sensitive.

PRODUCT: Emzone G24 Tech Lube - 320g**CODE: 045024****SECTION 06: ACCIDENTAL RELEASE MEASURES**

Spills and Leaks..... Put on appropriate personal protective equipment (see Section 08). Eliminate all sources of ignition and ventilate area. Contain spillage, and then collect with non-combustible absorbent material (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see Section 13).

SECTION 07: HANDLING AND STORAGE

Precautions for Safe Handling..... Do not breathe vapour or mist. Avoid contact with eyes, skin, and clothing. Keep container tightly closed. Use with adequate ventilation. Do not place near sources of heat.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL NIOSH
Aliphatic Hydrocarbons	Not available 2000 ppm	Not available	Not available	Not available	Not available
Isobutane	800 ppm	1000 ppm	800ppm	Not available	800 ppm (TWA)
Propane	2,500 ppm	Not available	1,000 ppm	Not available	1,000 ppm
Eye/Face Protection.....	Do not get in eyes. Wear safety glasses with side-shields.				
Skin Protection.....	Normally, no hand protection is required; however, prolonged or repeated contact with skin use chemical resistant gloves conforming to appropriate regulations. Observe the instructions regarding permeability and breakthrough time that are provided by the supplier of the gloves.				
Respiratory Protection.....	Typical use of this product under normal conditions does not require the use of respiratory protection. If airborne concentrations are above the applicable exposure limits (listed below), use NIOSH approved respiratory protection .				
Appropriate Engineering Controls.....	Good general ventilation should be used. Ventilation rates should be matched to conditions. Use local exhaust ventilation to maintain airborne levels below the Threshold Limit Value.				
Exposure Limits					

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Physical State..... Aerosol.
 Physical Appearance..... Light Brown.
 Odour..... Odourless.
 Odour Threshold (ppm)..... Not determined.
 pH..... Not applicable.
 Internal can pressure @21C (psig) 70-90 .
 Vapour Density (Air=1)..... > 1.
 Evaporation Rate (n-Butyl Acetate = 1)..... Not available.
 Initial Boiling Point/Boiling Range (°C)..... Not available.
 VOC Content..... > 95 wt%.
 Specific Gravity (Liquid)..... 0.880-0.920.
 Specific Gravity (Aerosol)..... 0.980-1.020 .
 Solubility in water..... Nil.
 Aerosol Flame Projection..... Not available .
 Auto Ignition Temperature (Propellant), °C... 460°C (860°F).
 Flashback..... No data .
 Flash Point (°C), Method..... -83.15°C/ -117.7°F.
 Lower Flammable Limit (% Vol)..... 1.8.
 Upper Flammable Limit (% Vol)..... 9.5.

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability..... Stable under the recommended storage and handling conditions.
 Incompatible Materials..... Strong oxidizing agents.
 Conditions to Avoid..... Avoid sources of heat and flame, and electrostatic charge.
 Hazardous Decomposition Products..... May form carbon dioxide and carbon monoxide, various hydrocarbons.
 Possibility of Hazardous Reactions..... Will not occur.

PRODUCT: Emzone G24 Tech Lube - 320g**CODE: 045024****SECTION 11: TOXICOLOGICAL INFORMATION**

INGREDIENTS	LC50	LD50
Aliphatic Hydrocarbons	Not available	Not available
Isobutane	658 mg/L (Rat,4hrs)	Not available
Propane	>800,000 ppm (Rat,15min)	Not available
Route of Exposure.....	Eye contact, Skin contact, Skin absorption, Inhalation, and Ingestion.	
Effects of Acute Exposure.....	High vapor/aerosol concentrations may be irritating to eyes. Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping. In high concentrations, vapors and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Ingestion may result in vomiting.	
Chronic Effects.....	Organic solvents may be absorbed into the body by inhalation and ingestion and cause permanent damage to the nervous system, including the brain. Prolong contact may defat and dry the skin, leading to discomfort and dermatitis.	
Carcinogenicity.....	Not classified as carcinogenic by ACGIH, IARC, OSHA or NTP.	
Reproductive Toxicity.....	No information is available, and no adverse effects are expected.	
Teratogenicity.....	No information is available, and no adverse effects are expected.	
Germ Cell Mutagenicity.....	No information is available, and no adverse effects are expected.	
Toxicological Data		

SECTION 12: ECOLOGICAL INFORMATION

Environmental..... Complete information is not yet available. This product has not been tested. Based on information available on its ingredients, no adverse environmental impact is anticipated under intended use in accordance with instructions. Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods..... Dispose in accordance with local, provincial and federal regulations.

SECTION 14: TRANSPORT INFORMATION

TDG (Canada- Road)..... AEROSOLS, Class 2.1, UN1950.
 DOT (US-Road)..... AEROSOLS, Class 2.1, UN1950, LTD QTY, Consumer commodity ORM-D.
 IMDG (International- Marine)..... AEROSOLS, Class 2.1, UN1950.
 IATA (International- Air)..... AEROSOLS, Class 2.1, UN1950, LTD QTY.

SECTION 15: REGULATORY INFORMATION

Canada Regulations:..... WHMIS Classification. A: Compressed gas. B5: Flammable Aerosol. D2B: Material causing other toxic Materials. CPR (Canadian Controlled Product Regulations): All ingredients are CEPA approved for import to Canada. This product has been classified in accordance with the hazard criteria of the CPR and this SDS contains all information required by CPR. IDL (Canadian Ingredient Disclosure List): Component(s) of this product identified by CAS number and listed on the Canadian Ingredient Disclosure List (section 03).
 US Regulations..... Environmental Protection Act: Constituents of this product are included on the TSCA inventory. HMIS classification see section 01. OSHA (29CFR 1910.1200).

SECTION 16: OTHER INFORMATION

Disclaimer..... The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Empack assumes no responsibility for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR. THIS SDS IS VALID FOR THREE YEARS.
 Abbreviations..... ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.
 Prepared by Regulatory Affairs
 Latest Revision FEB 28/2017