

Tire Fitting Lubricant, 5 kg

Version 4.0	Revision Date: 01/07/2019	SDS Number: 1459120-00006	Date of last issue: 08/10/2018 Date of first issue: 02/06/2014
----------------	------------------------------	------------------------------	---

SECTION 1. IDENTIFICATION

Product name : Tire Fitting Lubricant, 5 kg

Product code : 890.1221

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : CANUTEC (24/7): +1 (613) 996-6666 or/ou *666 (cellular/cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Anti-friction agent and lubricant

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

|| Not a hazardous substance or mixture.

GHS label elements

|| Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Stearic acid	57-11-4	≥ 30 - < 60
Sodium stearate	822-16-2	≥ 10 - < 30
Diethylene glycol	111-46-6	≥ 5 - < 10

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 08/10/2018
4.0	01/07/2019	1459120-00006	Date of first issue: 02/06/2014

- | | | |
|---|---|---|
| If inhaled | : | If inhaled, remove to fresh air.
Get medical attention if symptoms occur. |
| In case of skin contact | : | Wash with water and soap as a precaution.
Get medical attention if symptoms occur. |
| In case of eye contact | : | Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists. |
| If swallowed | : | If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water. |
| Most important symptoms and effects, both acute and delayed | : | None known. |
| Protection of first-aiders | : | No special precautions are necessary for first aid responders. |
| Notes to physician | : | Treat symptomatically and supportively. |

SECTION 5. FIRE-FIGHTING MEASURES

- | | | |
|--|---|---|
| Suitable extinguishing media | : | Water spray
Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : | None known. |
| Specific hazards during fire fighting | : | Exposure to combustion products may be a hazard to health. |
| Hazardous combustion products | : | Carbon oxides
Metal oxides |
| Specific extinguishing methods | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area. |
| Special protective equipment for fire-fighters | : | Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | | |
|---|---|--|
| Personal precautions, protective equipment and emergency procedures | : | Follow safe handling advice and personal protective equipment recommendations. |
|---|---|--|

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 08/10/2018
4.0	01/07/2019	1459120-00006	Date of first issue: 02/06/2014

II

- Environmental precautions : Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g., by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment. Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers. Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Stearic acid	57-11-4	TWA (Inhalable fraction)	10 mg/m ³	ACGIH
		TWA (Respirable fraction)	3 mg/m ³	ACGIH

Tire Fitting Lubricant, 5 kg

Version 4.0 Revision Date: 01/07/2019 SDS Number: 1459120-00006 Date of last issue: 08/10/2018
 Date of first issue: 02/06/2014

Sodium stearate	822-16-2	TWA	10 mg/m ³	CA AB OEL
		TWA	10 mg/m ³	CA BC OEL
		TWA (Inhalable fraction)	10 mg/m ³	ACGIH
		TWA (Respirable fraction)	3 mg/m ³	ACGIH

Engineering measures : Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations. Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m³ - total dust, 5 mg/m³ - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m³ - respirable particles, 10 mg/m³ - inhalable particles.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapor type

Hand protection
Material : Natural Rubber

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Eye protection : Wear the following personal protective equipment:
Safety glasses
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.
Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.

Skin and body protection : Skin should be washed after contact.

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 08/10/2018
4.0	01/07/2019	1459120-00006	Date of first issue: 02/06/2014

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	paste
Color	:	white
Odor	:	mild
Odor Threshold	:	No data available
pH	:	ca. 8 (20 °C) (as an emulsion)
Melting point/freezing point	:	ca. 50 °C
Initial boiling point and boiling range	:	No data available
Flash point	:	ca. 240 °C Method: DIN 51376
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	No data available
Density	:	1.06 g/cm ³ (20 °C)
Solubility(ies) Water solubility	:	completely miscible
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	ca. 400 °C
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	No data available

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 08/10/2018
4.0	01/07/2019	1459120-00006	Date of first issue: 02/06/2014

Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Can react with strong oxidizing agents.
Conditions to avoid	:	None known.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

|| Not classified based on available information.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
---------------------	---	--

Components:**Stearic acid:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	LC50 (Rat): > 2 mg/l Exposure time: 1 h Test atmosphere: vapor Remarks: Based on data from similar materials
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity

Sodium stearate:

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 08/10/2018
4.0	01/07/2019	1459120-00006	Date of first issue: 02/06/2014

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Remarks: Based on data from similar materials

Diethylene glycol:

Acute oral toxicity : Acute toxicity estimate (Humans): 1,120 mg/kg
Method: Expert judgment

Skin corrosion/irritation

|| Not classified based on available information.

Components:**Stearic acid:**

Species : Rabbit
Method : Patch Test 24 Hrs.
Result : No skin irritation

Sodium stearate:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Diethylene glycol:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

|| Not classified based on available information.

Components:**Stearic acid:**

Species : Rabbit
Result : No eye irritation

Sodium stearate:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Diethylene glycol:

Species : Rabbit
Result : No eye irritation

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 08/10/2018
4.0	01/07/2019	1459120-00006	Date of first issue: 02/06/2014

Respiratory or skin sensitization**Skin sensitization**

|| Not classified based on available information.

Respiratory sensitization

|| Not classified based on available information.

Components:**Stearic acid:**

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative
Remarks	:	Based on data from similar materials

Sodium stearate:

Test Type	:	Human repeat insult patch test (HRIPT)
Routes of exposure	:	Skin contact
Result	:	negative
Remarks	:	Based on data from similar materials

Diethylene glycol:

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	Directive 67/548/EEC, Annex V, B.6.
Result	:	negative

Germ cell mutagenicity

|| Not classified based on available information.

Components:**Stearic acid:**

Genotoxicity in vitro	:	Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative Remarks: Based on data from similar materials
-----------------------	---	--

	:	Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative Remarks: Based on data from similar materials
--	---	---

	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative Remarks: Based on data from similar materials
--	---	---

Sodium stearate:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471
-----------------------	---	---

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 08/10/2018
4.0	01/07/2019	1459120-00006	Date of first issue: 02/06/2014

Result: negative
Remarks: Based on data from similar materials

Diethylene glycol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-
malian cells
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

|| Not classified based on available information.

Components:**Diethylene glycol:**

Species	: Rat
Application Route	: Ingestion
Exposure time	: 108 weeks
Result	: negative

Reproductive toxicity

|| Not classified based on available information.

Components:**Stearic acid:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the
reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the
reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 08/10/2018
4.0	01/07/2019	1459120-00006	Date of first issue: 02/06/2014

Diethylene glycol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Mouse
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rabbit
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

STOT-single exposure

|| Not classified based on available information.

STOT-repeated exposure

|| Not classified based on available information.

Repeated dose toxicity**Components:****Stearic acid:**

Species : Rat
NOAEL : 1,000 mg/kg
Application Route : Ingestion
Exposure time : 42 Days
Method : OECD Test Guideline 422
Remarks : Based on data from similar materials

Diethylene glycol:

Species : Rat
NOAEL : 300 mg/kg
Application Route : Ingestion
Exposure time : 98 Days

Species : Dog
NOAEL : 2,220 mg/kg
Application Route : Skin contact
Exposure time : 4 Weeks
Method : OECD Test Guideline 410
Remarks : Based on data from similar materials

Aspiration toxicity

|| Not classified based on available information.

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 08/10/2018
4.0	01/07/2019	1459120-00006	Date of first issue: 02/06/2014

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Stearic acid:**

- Toxicity to fish : LL50 (*Leuciscus idus* (Golden orfe)): > 10,000 mg/l
Exposure time: 48 h
Method: DIN 38412
- Toxicity to daphnia and other aquatic invertebrates : EL50 (*Daphnia magna* (Water flea)): > 10 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials
No toxicity at the limit of solubility.
- Toxicity to algae : NOELR (*Pseudokirchneriella subcapitata* (green algae)): > 10 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
No toxicity at the limit of solubility.
- EL50 (*Pseudokirchneriella subcapitata* (green algae)): > 1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
No toxicity at the limit of solubility.
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (*Daphnia magna* (Water flea)): > 0.5 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials
No toxicity at the limit of solubility.
- Toxicity to microorganisms : EC10 (*Pseudomonas putida*): 883 mg/l
Exposure time: 18 h

Sodium stearate:

- Toxicity to fish : LL50 (*Leuciscus idus* (Golden orfe)): > 100 mg/l
Exposure time: 48 h
Method: DIN 38412
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EL50 (*Daphnia magna* (Water flea)): > 1 mg/l
Exposure time: 47 h
Test substance: Water Accommodated Fraction
Method: Directive 67/548/EEC, Annex V, C.2.
Remarks: Based on data from similar materials
No toxicity at the limit of solubility.
- Toxicity to algae : EL50 (*Pseudokirchneriella subcapitata* (green algae)): > 1

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 08/10/2018
4.0	01/07/2019	1459120-00006	Date of first issue: 02/06/2014

mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
No toxicity at the limit of solubility.

NOELR (*Pseudokirchneriella subcapitata* (green algae)): > 1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC10 (*Pseudomonas putida*): > 100 mg/l
Exposure time: 16 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Diethylene glycol:

Toxicity to fish : LC50 (*Pimephales promelas* (fathead minnow)): 75,200 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): > 10,000 mg/l
Exposure time: 24 h
Method: DIN 38412

Toxicity to algae : NOEC (*Pseudokirchneriella subcapitata* (green algae)): > 1 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC (*Pimephales promelas* (fathead minnow)): > 1 mg/l
Exposure time: 7 d
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (*Daphnia magna* (Water flea)): > 1 mg/l
Exposure time: 21 d
Remarks: Based on data from similar materials

Persistence and degradability**Components:****Stearic acid:**

Biodegradability : Result: Readily biodegradable.
Biodegradation: 71 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Sodium stearate:

Biodegradability : Result: Readily biodegradable.
Remarks: Based on data from similar materials

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 08/10/2018
4.0	01/07/2019	1459120-00006	Date of first issue: 02/06/2014

Diethylene glycol:

Biodegradability : Result: Readily biodegradable.

Bioaccumulative potential**Components:****Stearic acid:**

Partition coefficient: n-octanol/water : log Pow: 8.23

Sodium stearate:

Partition coefficient: n-octanol/water : log Pow: > 4

Diethylene glycol:Partition coefficient: n-octanol/water : log Pow: -1.98
Remarks: Calculation**Mobility in soil**

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 08/10/2018
4.0	01/07/2019	1459120-00006	Date of first issue: 02/06/2014

TDG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products
VOC content: 0 % / 0 g/l

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	: Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	: Canada. British Columbia OEL
ACGIH / TWA	: 8-hour, time-weighted average
CA AB OEL / TWA	: 8-hour Occupational exposure limit
CA BC OEL / TWA	: 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 08/10/2018
4.0	01/07/2019	1459120-00006	Date of first issue: 02/06/2014

Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 01/07/2019

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8