

SAFETY DATA SHEET



Car Brite™ EASI-OFF YELLOW Paste Wax

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2018
1.5	05/06/2018	600000000824	Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : EASIOFF YELLOW PASTE WAX 16 OC 1 UN

Product code : CBO1A010-01

Manufacturer or supplier's details

Company name of supplier : Niteo Products,LLC

Address : Dallas TX 19162

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Recommended use of the chemical and restrictions on use

Recommended use : CLEANER

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin irritation : Category 2

Specific target organ toxicity : Category 3 (Central nervous system)
- single exposure

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air

Car Brite™ EASI-OFF YELLOW Paste Wax

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2018
1.5	05/06/2018	600000000824	Date of first issue: 05/23/2016

and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC	64742-88-7	>= 50 - < 70
KEROSENE	8008-20-6	>= 20 - < 30

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Move to fresh air. Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: If on clothes, remove clothes. Remove contaminated clothing. If irritation develops, get medical attention. If on skin, rinse well with water. Wash contaminated clothing before re-use. If skin irritation persists, call a physician.
In case of eye contact	: Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing.
If swallowed	: Do not give milk or alcoholic beverages.

SAFETY DATA SHEET



Car Brite™ EASI-OFF YELLOW Paste Wax

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2018
1.5	05/06/2018	600000000824	Date of first issue: 05/23/2016

Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : Causes skin irritation.
May cause drowsiness or dizziness.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire-fighting : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.
Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides
Silicon oxides

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Avoid dust formation.
Avoid breathing dust.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Car Brite™ EASI-OFF YELLOW Paste Wax

Version	Revision Date:	SDS Number:	Date of last issue:
1.5	05/06/2018	600000000824	04/12/2018
			Date of first issue: 05/23/2016

- Advice on protection against fire and explosion : Take measures to prevent the build up of electrostatic charge. Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
- Advice on safe handling : Avoid creating dust. Provide sufficient air exchange and/or exhaust in work rooms. Do not breathe vapours/dust. Do not smoke. Avoid contact with skin and eyes. Dispose of rinse water in accordance with local and national regulations. Container hazardous when empty. Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
KEROSENE	8008-20-6	TWA	100 mg/m ³	NIOSH REL

Hazardous components without workplace control parameters

Components	CAS-No.
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC	64742-88-7

- Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects. Provide appropriate exhaust ventilation at places where dust is formed.

Personal protective equipment

- Respiratory protection : In the case of dust or aerosol formation use respirator with an approved filter.

Hand protection

- Remarks : Wear resistant gloves (consult your safety equipment supplier)

SAFETY DATA SHEET



Car Brite™ EASI-OFF YELLOW Paste Wax

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2018
1.5	05/06/2018	600000000824	Date of first issue: 05/23/2016

er). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.

Eye protection	:	Safety glasses
Skin and body protection	:	Choose body protection according to the amount and concentration of the dangerous substance at the work place. Wear as appropriate: Safety shoes
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust. When using do not smoke. When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	paste
Colour	:	yellow
Odour	:	pleasant
pH	:	No data available
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	35 °C (1,013 hPa) The value is calculated
Flash point	:	73.8 °C Method: closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	7 %(V) The value is calculated
Lower explosion limit / Lower flammability limit	:	0.7 %(V) The value is calculated
Vapour pressure	:	6.67 hPa (20 °C) The value is calculated
Density	:	0.871 g/cm3
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-	:	No data available

Car Brite™ EASI-OFF YELLOW Paste Wax

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2018
1.5	05/06/2018	600000000824	Date of first issue: 05/23/2016

octanol/water

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Hazardous polymerisation does not occur.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products :

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**Inhalation
Skin contact
Eye contact
Ingestion**Acute toxicity**

Not classified based on available information.

Product:Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method**Components:****SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.28 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: No adverse effect has been observed in acute

SAFETY DATA SHEET



Car Brite™ EASI-OFF YELLOW Paste Wax

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2018
1.5	05/06/2018	600000000824	Date of first issue: 05/23/2016

dermal toxicity tests.

KEROSENE:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 420

Acute inhalation toxicity : LC50 (Rat): > 5.8 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:

SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC:

Species: Rabbit
Result: Skin irritation

KEROSENE:

Result: Irritating to skin.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Product dust may be irritating to eyes, skin and respiratory system.

Components:

SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC:

Species: Rabbit
Result: No eye irritation

KEROSENE:

Result: Possibly irritating to eyes

Car Brite™ EASI-OFF YELLOW Paste Wax

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2018
1.5	05/06/2018	600000000824	Date of first issue: 05/23/2016

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:**SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC:**

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Components:**SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC:**

Genotoxicity in vitro	:	Test Type: Ames test
		Test system: Salmonella typhimurium
		Metabolic activation: with and without metabolic activation
		Result: negative

Carcinogenicity

Not classified based on available information.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
-------------	---

OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
-------------	--

NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
------------	---

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:**SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC:**

Exposure routes: inhalation (vapour)

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

KEROSENE:

Assessment: May cause drowsiness or dizziness.

Car Brite™ EASI-OFF YELLOW Paste Wax

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2018
1.5	05/06/2018	600000000824	Date of first issue: 05/23/2016

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:**SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

KEROSENE:

May be fatal if swallowed and enters airways.

Further information**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12. ECOLOGICAL INFORMATION

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations**IATA-DGR**

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SAFETY DATA SHEET



Car Brite™ EASI-OFF YELLOW Paste Wax

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2018
1.5	05/06/2018	600000000824	Date of first issue: 05/23/2016

National Regulations

49 CFR

Not regulated as a dangerous good

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Skin corrosion or irritation
Specific target organ toxicity (single or repeated exposure)

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations


California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



SAFETY DATA SHEET



Car Brite™ EASI-OFF YELLOW Paste Wax

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2018
1.5	05/06/2018	600000000824	Date of first issue: 05/23/2016

Revision Date : 05/06/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN