

Material Safety Data Sheet

Print Date: 01/29/2019

Revision Date : 06/24/2014

Page 1 of 11

Commercial Product Name: **ATF**

Part number: G 052162A2

Version : 2.0

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name	:	ATF
MSDS Number	:	888100000059
Product Use Description	:	Gear oil
Company	:	Volkswagen Canada, Inc. 777 Bayly Street West Ajax, Ontario Canada L1S 7G7
Telephone	:	248 754 4944 8:00 am. – 5:00 pm. EST
Telefax	:	248 754 4943
Emergency telephone number	:	631 996 6666

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Regulatory status : This product, material or substance is a WHMIS controlled product per Sections 33 - 66, Part IV of the CPR.

Signal Word	:	CAUTION
Form	:	liquid
Colour	:	amber
Odour	:	characteristic
Odour - Control parameters	:	No data available
Hazard Summary	:	Irritant

Potential Health Effects

Skin	:	May cause skin irritation.
Eyes	:	May cause eye irritation.

Material Safety Data Sheet

Print Date: 01/29/2019

Revision Date : 06/24/2014

Page 2 of 11

Commercial Product Name: **ATF**

Part number: G 052162A2

Version : 2.0

Target Organs : Skin
Eyes

Carcinogenicity:
ACGIH : No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP : No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC : No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA : No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

CA Prop 65 : This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Weight percent
1-Decene, homopolymer, hydrogenated	68037-01-4	>= 25 - < 35
White mineral oil (petroleum)	8042-47-5	>= 25 - < 35
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified	64742-65-0	>= 20 - < 25

Material Safety Data Sheet

Print Date: 01/29/2019

Revision Date : 06/24/2014

Page 3 of 11

Commercial Product Name: **ATF**

Part number: G 052162A2

Version : 2.0

SECTION 4. FIRST AID MEASURES

- | | |
|----------------|---|
| General advice | : If you feel unwell, seek medical advice (show the label where possible). Remove from exposure, lie down. Never give anything by mouth to an unconscious person. Take off all contaminated clothing immediately. Wash contaminated clothing before re-use. |
| Inhalation | : Remove to fresh air. Keep patient warm and at rest. In the case of inhalation of aerosol/mist consult a physician if necessary. |
| Skin contact | : Wash off immediately with soap and plenty of water. |
| Eye contact | : Remove contact lenses. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. |
| Ingestion | : If swallowed, seek medical advice immediately and show this container or label. Do NOT induce vomiting. |

SECTION 5. FIREFIGHTING MEASURES

- | | |
|--|--|
| Form | : liquid |
| Flash point | : $\geq 180^{\circ}\text{C}$ (356°F) |
| Lower explosion limit | : 0.9 %(V) |
| Upper explosion limit | : 7.0 %(V) |
| Suitable extinguishing media | : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. |
| Extinguishing media which shall not be used for safety reasons | : High volume water jet |

Material Safety Data Sheet

Print Date: 01/29/2019

Revision Date : 06/24/2014

Page 4 of 11

Commercial Product Name: **ATF**

Part number: G 052162A2

Version : 2.0

Specific hazards during firefighting : Fire will produce dense black smoke containing hazardous combustion products (see section 10).
Exposure to decomposition products may be a hazard to health.

Special protective equipment for firefighters : Use personal protective equipment.

Further information : Standard procedure for chemical fires.
In the event of fire and/or explosion do not breathe fumes.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Refer to protective measures listed in sections 7 and 8.
Ensure adequate ventilation, especially in confined areas.

Environmental precautions : Try to prevent the material from entering drains or water courses.
Avoid subsoil penetration.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods for cleaning up : Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations.

Additional advice : Contaminated surfaces will be extremely slippery.

Material Safety Data Sheet

Print Date: 01/29/2019

Revision Date : 06/24/2014

Page 5 of 11

Commercial Product Name: **ATF**

Part number: G 052162A2

Version : 2.0

SECTION 7. HANDLING AND STORAGE

Handling

Handling : Avoid contact with skin and eyes.
 Avoid formation of aerosol.
 For personal protection see section 8.

Advice on protection : Normal measures for preventive fire protection.
 against fire and explosion

Dust explosion class : Not applicable

Storage

Requirements for storage : Keep containers tightly closed in a dry, cool and well-ventilated
 areas and containers place.

Advice on common storage : Keep away from food, drink and animal feedingstuffs.

Other data : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Components	CAS-No.	List	Type:	Value	Update
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified	64742-65-0	CA BC OEL	TWA	1 mg/m3	2012-04-20
		CA BC OEL	TWA	0.2 mg/m3	2012-04-20

Material Safety Data Sheet

Print Date: 01/29/2019

Revision Date : 06/24/2014

Page 6 of 11

Commercial Product Name: **ATF**

Part number: G 052162A2

Version : 2.0

		CA AB OEL	TWA	5 mg/m3	2009-04-30
		CA AB OEL	STEL	10 mg/m3	2009-04-30
		CA QC OEL	TWAEV	5 mg/m3	2012-11-28
		CA QC OEL	STEV	10 mg/m3	2012-11-28
Distillates (petroleum), solvent-refined light paraffinic; Baseoil - unspecified	64741-89-5	CA BC OEL	TWA	1 mg/m3	2012-04-20
		CA BC OEL	TWA	0.2 mg/m3	2012-04-20
		CA AB OEL	TWA	5 mg/m3	2009-04-30
		CA AB OEL	STEL	10 mg/m3	2009-04-30
		CA QC OEL	TWAEV	5 mg/m3	2012-11-28
		CA QC OEL	STEV	10 mg/m3	2012-11-28

Engineering measures : Provide adequate ventilation.

Eye protection : Safety glasses

Hand protection : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work.
For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer.

Skin and body protection : Long sleeved clothing

Respiratory protection : Not required; except in case of aerosol formation.
Respirator with filter type A

Hygiene measures : Avoid contact with the skin and the eyes.

Material Safety Data Sheet

Print Date: 01/29/2019

Revision Date : 06/24/2014

Page 7 of 11

Commercial Product Name: **ATF**

Part number: G 052162A2

Version : 2.0

When using do not eat, drink or smoke.

Wash hands before breaks and at the end of workday.

Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: liquid
Colour	: amber
Odour	: characteristic
Flash point	: $\geq 180^{\circ} \text{C}$ (356°F)
Lower explosion limit	: 0.9 %(V)
Upper explosion limit	: 7.0 %(V)
pH	: Not applicable
Melting point/range	: Not applicable
pour point	: $< -48^{\circ} \text{C}$ ($< -54^{\circ} \text{F}$)
Solidification / Setting point	: No data available
Boiling point/boiling range	: $> 316^{\circ} \text{C}$ ($> 601^{\circ} \text{F}$)
Vapour pressure	: $< 0.013 \text{ kPa}$ at 20°C (68°F)
Density	: 0.855 g/cm^3 at 15°C (59°F)
Water solubility	: negligible

Material Safety Data Sheet

Print Date: 01/29/2019

Revision Date : 06/24/2014

Page 8 of 11

Commercial Product Name: **ATF**

Part number: G 052162A2

Version : 2.0

Viscosity, kinematic : 7.4 mm²/s
at 100 ° C (212 ° F)

Viscosity, kinematic : 37.2 mm²/s
at 40 ° C (104 ° F)

Volatile organic compounds : 0 %
(VOC) content

SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid : Heat.

Materials to avoid : Strong oxidizing agents

Hazardous decomposition : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of
products nitrogen (NO_x), dense black smoke.

Hazardous reactions : Note: Stable under recommended storage conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity : LD50 Rat
Dose: > 5,000 mg/kg
Data from similar compositions

Acute dermal toxicity : LD50 Rat
Dose: > 5,000 mg/kg
Data from similar compositions

Acute inhalation toxicity : LC50 Rat
Dose: > 5 mg/l
Data from similar compositions

Material Safety Data Sheet

Print Date: 01/29/2019

Revision Date : 06/24/2014

Page 9 of 11

Commercial Product Name: **ATF**

Part number: G 052162A2

Version : 2.0

- Skin irritation : Result: Mild skin irritation
Prolonged skin contact may cause skin irritation.
- Eye irritation : Result: Mild eye irritation
May irritate eyes.
- Carcinogenicity : No data is available on the product itself.
- Reproductive toxicity : No data is available on the product itself.
- Teratogenicity : No data is available on the product itself.
- Further information : Ingestion may cause gastrointestinal irritation, nausea,
vomiting and diarrhoea.

Component:

Distillates (petroleum), solvent- 64742-65-0
dewaxed heavy paraffinic; Baseoil
- unspecified

Acute oral toxicity: LD50 Rat
Dose: > 5,000 mg/kg

Acute dermal toxicity: LD50 Rabbit
Dose: > 5,000 mg/kg

Acute inhalation toxicity: LC50 Rat
Dose: 4 mg/l
Exposure time: 4 h

Skin irritation: Classification: Irritating to skin.
Result: Mild skin irritation

Eye irritation: Classification: Irritating to eyes.
Result: Mild eye irritation

SECTION 12. ECOLOGICAL INFORMATION

- Adsorbed organic bound : not included
halogens (AOX)
- Volatile organic compounds : 0 %

Material Safety Data Sheet

Print Date: 01/29/2019

Revision Date : 06/24/2014

Page 10 of 11

Commercial Product Name: **ATF**

Part number: G 052162A2

Version : 2.0

(VOC) content

Additional ecological information : The product should not be allowed to enter drains, water courses or the soil.

SECTION 13. DISPOSAL CONSIDERATIONS

Adequate disposal : In accordance with local and national regulations.

SECTION 14. TRANSPORT INFORMATION

DOT 49 CFR

Not dangerous goods

TDGR

Not dangerous goods

ICAO / IATA-DGR

Not dangerous goods

IMDG-Code

Not dangerous goods

SECTION 15. REGULATORY INFORMATION

TSCA Status : On TSCA Inventory

DSL Status : All components of this product are on the Canadian DSL.

Material Safety Data Sheet

Print Date: 01/29/2019

Revision Date : 06/24/2014

Page 11 of 11

Commercial Product Name: **ATF**

Part number: G 052162A2

Version : 2.0

California Prop. 65 : This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

WHMIS Classification : D2B Toxic Material Causing Other Toxic Effects
Moderate skin irritant
Moderate eye irritant

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

SECTION 16. OTHER INFORMATION

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Prepared by : SAP Business Compliance Services GmbH
Birlenbacher Str. 19
D-57078 Siegen
Germany

Telephone: +49-(0)271-88072-0

Revision Date : 06/24/2014