

Gear oil

Version	Revision Date:	SDS Number:	Date of last issue: 09/26/2018
5.0	09/26/2018	1365002-00003	Date of first issue: 03/20/2007

SECTION 1. IDENTIFICATION

Product name : Gear oil

Product code : G 052512A2

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Volkswagen Canada, Inc.

Address : 777 Bayly Street West
Ajax Ontario Canada, L1S 7G7

Telephone : 248 754 4944

Telefax : 248 754 4943

Emergency telephone : 631 996 6666

Recommended use of the chemical and restrictions on use

Recommended use : Gear oil

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Skin sensitization : Category 1

GHS label elements

Hazard pictograms	: 
Signal Word	: Warning
Hazard Statements	: H317 May cause an allergic skin reaction.
Precautionary Statements	: Prevention: P261 Avoid breathing mist or vapors. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves. Response: P302 + P352 IF ON SKIN: Wash with plenty of water. P333 + P313 If skin irritation or rash occurs: Get medical advice/attention. P362 + P364 Take off contaminated clothing and wash it before reuse.

Gear oil

Version 5.0 Revision Date: 09/26/2018 SDS Number: 1365002-00003 Date of last issue: 09/26/2018
Date of first issue: 03/20/2007

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	$\geq 60 - < 80$
Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified	64742-56-9	$\geq 10 - < 30$
Phosphoric acid esters-amine salt	Not Assigned	$\geq 0.1 - < 1$
Bis(2-hydroxyethyl)tallowamine	61791-44-4	$\geq 0.1 - < 1$

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment

Gear oil

Version	Revision Date:	SDS Number:	Date of last issue: 09/26/2018
5.0	09/26/2018	1365002-00003	Date of first issue: 03/20/2007

when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

Gear oil

Version	Revision Date:	SDS Number:	Date of last issue: 09/26/2018
5.0	09/26/2018	1365002-00003	Date of first issue: 03/20/2007

employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Avoid inhalation of vapor or mist.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist)	5 mg/m ³	CA QC OEL
		STEV (Mist)	10 mg/m ³	CA QC OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified	64742-56-9	TWA (Inhalable fraction)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist)	5 mg/m ³	CA QC OEL
		STEV (Mist)	10 mg/m ³	CA QC OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL

Gear oil

Version 5.0 Revision Date: 09/26/2018 SDS Number: 1365002-00003 Date of last issue: 09/26/2018
Date of first issue: 03/20/2007

		TWA (Inhalable fraction)	5 mg/m ³	ACGIH
--	--	--------------------------------	---------------------	-------

Engineering measures : Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapor type

Hand protection
Material : Nitrile rubber

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : dark yellow

Odor : characteristic

Odor Threshold : No data available

pH : No data available

Gear oil

Version	Revision Date:	SDS Number:	Date of last issue: 09/26/2018
5.0	09/26/2018	1365002-00003	Date of first issue: 03/20/2007

Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	212 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Density	:	0.876 g/cm ³ (15 °C)
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, kinematic	:	35.3 mm ² /s (40 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Can react with strong oxidizing agents.

Gear oil

Version	Revision Date:	SDS Number:	Date of last issue: 09/26/2018
5.0	09/26/2018	1365002-00003	Date of first issue: 03/20/2007

Conditions to avoid	:	None known.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:**Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401 Remarks: Based on data from similar materials
Acute inhalation toxicity	:	LC50 (Rat): > 5.53 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Method: OECD Test Guideline 402 Remarks: Based on data from similar materials

Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	LC50 (Rat): > 5.53 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Method: OECD Test Guideline 402

Phosphoric acid esters-amine salt:

Acute oral toxicity	:	LD50 (Rat): 2,000 mg/kg
---------------------	---	-------------------------

Gear oil

Version	Revision Date:	SDS Number:	Date of last issue: 09/26/2018
5.0	09/26/2018	1365002-00003	Date of first issue: 03/20/2007

Bis(2-hydroxyethyl)tallowamine:

Acute oral toxicity	: LD50 (Rat): 630 mg/kg
Acute inhalation toxicity	: Assessment: Corrosive to the respiratory tract.
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:**Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Species	: Rabbit
Result	: No skin irritation
Remarks	: Based on data from similar materials

Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified:

Species	: Rabbit
Result	: No skin irritation

Phosphoric acid esters-amine salt:

Species	: Rabbit
Result	: No skin irritation

Bis(2-hydroxyethyl)tallowamine:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: Corrosive after 1 to 4 hours of exposure

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405
Remarks	: Based on data from similar materials

Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified:

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405

Phosphoric acid esters-amine salt:

Species	: Rabbit
Result	: Irreversible effects on the eye

Gear oil

Version	Revision Date:	SDS Number:	Date of last issue: 09/26/2018
5.0	09/26/2018	1365002-00003	Date of first issue: 03/20/2007

Bis(2-hydroxyethyl)tallowamine:

Species	: Rabbit
Result	: Irreversible effects on the eye
Method	: OECD Test Guideline 405
Remarks	: Based on data from similar materials

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:**Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative
Remarks	: Based on data from similar materials

Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified:

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

Phosphoric acid esters-amine salt:

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: positive

Assessment	: Probability or evidence of skin sensitization in humans
------------	---

Bis(2-hydroxyethyl)tallowamine:

Assessment	: Probability or evidence of skin sensitization in humans
------------	---

Germ cell mutagenicity

Not classified based on available information.

Components:**Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471
-----------------------	---

Gear oil

Version	Revision Date:	SDS Number:	Date of last issue: 09/26/2018
5.0	09/26/2018	1365002-00003	Date of first issue: 03/20/2007

	Result: negative
	Remarks: Based on data from similar materials
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
	Species: Mouse
	Application Route: Intraperitoneal injection
	Method: OECD Test Guideline 474
	Result: negative
	Remarks: Based on data from similar materials

Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES)
	Method: OECD Test Guideline 471
	Result: negative
	Remarks: Based on data from similar materials

Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
	Species: Mouse
	Application Route: Intraperitoneal injection
	Method: OECD Test Guideline 474
	Result: negative
	Remarks: Based on data from similar materials

Phosphoric acid esters-amine salt:

Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test
	Method: OECD Test Guideline 476
	Result: negative

Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
	Species: Mouse
	Application Route: Intraperitoneal injection
	Method: OECD Test Guideline 474
	Result: negative

Bis(2-hydroxyethyl)tallowamine:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES)
	Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: positive

Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
	Species: Mouse
	Application Route: Ingestion
	Method: OECD Test Guideline 474

Gear oil

Version	Revision Date:	SDS Number:	Date of last issue: 09/26/2018
5.0	09/26/2018	1365002-00003	Date of first issue: 03/20/2007

Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Carcinogenicity

Not classified based on available information.

Components:**Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Species : Mouse
Application Route : Skin contact
Exposure time : 78 weeks
Method : OECD Test Guideline 451
Result : negative

Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified:

Species : Mouse
Application Route : Skin contact
Exposure time : 78 weeks
Method : OECD Test Guideline 451
Result : negative
Remarks : Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:**Phosphoric acid esters-amine salt:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421
Result: negative

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421
Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Gear oil

Version	Revision Date:	SDS Number:	Date of last issue: 09/26/2018
5.0	09/26/2018	1365002-00003	Date of first issue: 03/20/2007

Repeated dose toxicity

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species	: Rabbit
NOAEL	: 1,000 mg/kg
Application Route	: Skin contact
Exposure time	: 4 Weeks
Method	: OECD Test Guideline 410
Remarks	: Based on data from similar materials

Species	: Rat
NOAEL	: > 980 mg/m ³
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 4 Weeks
Remarks	: Based on data from similar materials

Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified:

Species	: Rat
NOAEL	: 1,000 mg/kg
Application Route	: Skin contact
Exposure time	: 4 Weeks
Method	: OECD Test Guideline 410
Remarks	: Based on data from similar materials

Species	: Rat
NOAEL	: > 980 mg/m ³
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 4 Weeks
Remarks	: Based on data from similar materials

Phosphoric acid esters-amine salt:

Species	: Rat
NOAEL	: 150 mg/kg
LOAEL	: 500 mg/kg
Application Route	: Ingestion
Exposure time	: 28 Days

Aspiration toxicity

Not classified based on available information.

Components:

Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified:

May be fatal if swallowed and enters airways.

Gear oil

Version	Revision Date:	SDS Number:	Date of last issue: 09/26/2018
5.0	09/26/2018	1365002-00003	Date of first issue: 03/20/2007

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	:	EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201

Components:**Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
Toxicity to algae	:	EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 10 mg/l Exposure time: 21 d Method: OECD Test Guideline 211 Remarks: Based on data from similar materials
Toxicity to microorganisms	:	NOEC: > 1.93 mg/l Exposure time: 10 min Method: DIN 38 412 Part 8 Remarks: Based on data from similar materials

Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
------------------	---	--

Gear oil

Version	Revision Date:	SDS Number:	Date of last issue: 09/26/2018
5.0	09/26/2018	1365002-00003	Date of first issue: 03/20/2007

Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
Toxicity to algae	:	EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 10 mg/l Exposure time: 21 d Method: OECD Test Guideline 211 Remarks: Based on data from similar materials
Toxicity to microorganisms	:	NOEC: > 1.93 mg/l Exposure time: 10 min Method: DIN 38 412 Part 8 Remarks: Based on data from similar materials

Phosphoric acid esters-amine salt:

Toxicity to fish	:	LL50 (Oncorhynchus mykiss (rainbow trout)): 24 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): 91.4 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202
Toxicity to algae	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): 15 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 NOEC (Pseudokirchneriella subcapitata (green algae)): 1.7 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOELR (Daphnia magna (Water flea)): 0.12 mg/l Exposure time: 21 d Test substance: Water Accommodated Fraction Method: OECD Test Guideline 211
Toxicity to microorganisms	:	EC50: 2,433 mg/l Exposure time: 3 h Method: OECD Test Guideline 209

Gear oil

Version	Revision Date:	SDS Number:	Date of last issue: 09/26/2018
5.0	09/26/2018	1365002-00003	Date of first issue: 03/20/2007

Bis(2-hydroxyethyl)tallowamine:**Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Persistence and degradability**Components:****Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 8 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Phosphoric acid esters-amine salt:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 3.6 %
Exposure time: 28 d

Bioaccumulative potential**Components:****Phosphoric acid esters-amine salt:**

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 432 - 436
Method: OPPTS 850.1730

Partition coefficient: n-octanol/water : log Pow: 1.81 - 6

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

Gear oil

Version	Revision Date:	SDS Number:	Date of last issue: 09/26/2018
5.0	09/26/2018	1365002-00003	Date of first issue: 03/20/2007

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

The ingredients of this product are reported in the following inventories:

DSL : This product contains one or several components that are not on the Canadian DSL nor NDSL.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response

Gear oil

Version	Revision Date:	SDS Number:	Date of last issue: 09/26/2018
5.0	09/26/2018	1365002-00003	Date of first issue: 03/20/2007

Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/26/2018

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8