

SAFETY DATA SHEET



Car Brite™ HIGH GLOSS DRESSING CL High Gloss Tire Dressing

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2017
1.2	05/05/2018	600000000189	Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : HIGH GLOSS DRESSING CL PL 5 GA

Product code : 780711

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : Dallas TX 19162

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Recommended use of the chemical and restrictions on use

Recommended use : POLISH

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 2

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.

Precautionary statements : **Prevention:**
P210 Keep away from heat/sparks/open flames/hot surfaces.
No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.

SAFETY DATA SHEET



Car Brite™ HIGH GLOSS DRESSING CL High Gloss Tire Dressing

Version 1.2 Revision Date: 05/05/2018 SDS Number: 600000000189 Date of last issue: 05/02/2017
Date of first issue: 05/23/2016

P243 Take precautionary measures against static discharge.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	$\geq 70 - < 90$
n-HEPTANE	142-82-5	$\geq 1 - < 5$
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2	$\geq 1 - < 5$

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on clothes, remove clothes.
Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.

SAFETY DATA SHEET



Car Brite™ HIGH GLOSS DRESSING CL High Gloss Tire Dressing

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2017
1.2	05/05/2018	600000000189	Date of first issue: 05/23/2016

- If skin irritation persists, call a physician.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
- If swallowed : Obtain medical attention.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Carbon dioxide (CO₂)
Dry chemical
Alcohol-resistant foam
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
Silicon oxides
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Do not use a solid water stream as it may scatter and spread fire.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Ensure adequate ventilation.
Avoid breathing dust.

**Car Brite™ HIGH GLOSS DRESSING CL High
 Gloss Tire Dressing**

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2017
1.2	05/05/2018	600000000189	Date of first issue: 05/23/2016

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
 Evacuate personnel to safe areas.
 Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.
 Prevent product from entering drains.
 Do not flush into surface water or sanitary sewer system.
 If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
 Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.
 Keep away from open flames, hot surfaces and sources of ignition.
 Use only explosion-proof equipment.
 Do not spray on a naked flame or any incandescent material.

Advice on safe handling : Open drum carefully as content may be under pressure.
 Avoid formation of aerosol.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Do not breathe vapours/dust.
 Do not smoke.
 Take precautionary measures against static discharges.
 Avoid contact with skin and eyes.
 Dispose of rinse water in accordance with local and national regulations.
 Container hazardous when empty.
 Smoking, eating and drinking should be prohibited in the application area.
 For personal protection see section 8.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 No smoking.

Further information on storage : No decomposition if stored and applied as directed.

SAFETY DATA SHEET


**Car Brite™ HIGH GLOSS DRESSING CL High
Gloss Tire Dressing**

Version 1.2 Revision Date: 05/05/2018 SDS Number: 600000000189 Date of last issue: 05/02/2017
Date of first issue: 05/23/2016

age stability

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
n-HEPTANE	142-82-5	TWA	85 ppm 350 mg/m3	NIOSH REL
		C	440 ppm 1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		STEL	500 ppm 2,000 mg/m3	OSHA P0
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m3	NIOSH REL
		TWA	50 ppm 240 mg/m3	OSHA Z-1
		TWA	25 ppm 120 mg/m3	OSHA P0

Hazardous components without workplace control parameters

Components	CAS-No.
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2	Butoxyace-tic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g Creatinine	ACGIH BEI

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

SAFETY DATA SHEET



Car Brite™ HIGH GLOSS DRESSING CL High Gloss Tire Dressing

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2017
1.2	05/05/2018	600000000189	Date of first issue: 05/23/2016

Remarks	: Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
Skin and body protection	: Choose body protection according to the amount and concentration of the dangerous substance at the work place. Wear as appropriate: Impervious clothing Flame-resistant clothing Safety shoes
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. When using do not smoke. When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Odour	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: 95 °C The value is calculated
Flash point	: -2 °C Method: closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Self-ignition	: No data available
Upper explosion limit / Upper flammability limit	: 10.6 %(V) The value is calculated
Lower explosion limit / Lower flammability limit	: 1.1 %(V) The value is calculated
Vapour pressure	: 60 hPa (20 °C) The value is calculated
Density	: 0.726 g/cm3
Solubility(ies)	

SAFETY DATA SHEET



Car Brite™ HIGH GLOSS DRESSING CL High Gloss Tire Dressing

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2017
1.2	05/05/2018	600000000189	Date of first issue: 05/23/2016

Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	No data available
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	16.5 mm ² /s (40 °C)
Oxidizing properties	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Acids Aluminium Amines Ammonia Bases chlorates Chlorine salts of strong bases Strong oxidizing agents
Hazardous decomposition products	:	Carbon oxides Silicon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Eye contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 200 mg/l Exposure time: 4 h

SAFETY DATA SHEET



Car Brite™ HIGH GLOSS DRESSING CL High Gloss Tire Dressing

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2017
1.2	05/05/2018	600000000189	Date of first issue: 05/23/2016

Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:

Acute oral toxicity : LD50 (Rat): > 8,000 mg/kg

n-HEPTANE:

Acute oral toxicity : LD50 (Rat): Expected > 5,000 mg/kg
Remarks: Information given is based on data obtained from similar substances.

Acute inhalation toxicity : LC50 (Rat, male and female): > 29.29 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): Expected > 2,000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.
Remarks: Information given is based on data obtained from similar substances.

ETHYLENE GLYCOL MONOBUTYL ETHER:

Acute oral toxicity : LD50 (Guinea pig): 1,200 mg/kg

Acute inhalation toxicity : LC50 (Guinea pig): > 633 ppm
Exposure time: 1 h
Test atmosphere: dust/mist
Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 (Guinea pig): > 2,000 mg/kg
Assessment: The component/mixture is moderately toxic after single contact with skin.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May irritate skin.

Components:

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:

Result: Possibly irritating to skin

**Car Brite™ HIGH GLOSS DRESSING CL High
Gloss Tire Dressing**

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2017
1.2	05/05/2018	600000000189	Date of first issue: 05/23/2016

n-HEPTANE:

Result: Irritating to skin.

ETHYLENE GLYCOL MONOBUTYL ETHER:

Result: Irritating to skin.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:

Result: Possibly irritating to eyes

n-HEPTANE:

Result: Possibly irritating to eyes

ETHYLENE GLYCOL MONOBUTYL ETHER:

Result: Irritating to eyes.

Assessment: Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

n-HEPTANE:

Test Type: Maximisation Test

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

Remarks: Information given is based on data obtained from similar substances.

Germ cell mutagenicity

Not classified based on available information.

Components:

n-HEPTANE:

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects

ETHYLENE GLYCOL MONOBUTYL ETHER:

SAFETY DATA SHEET



Car Brite™ HIGH GLOSS DRESSING CL High Gloss Tire Dressing

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2017
1.2	05/05/2018	600000000189	Date of first issue: 05/23/2016

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Not classified based on available information.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

Components:

n-HEPTANE:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:

May be fatal if swallowed and enters airways.

n-HEPTANE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

**Car Brite™ HIGH GLOSS DRESSING CL High
Gloss Tire Dressing**

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2017
1.2	05/05/2018	600000000189	Date of first issue: 05/23/2016

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues	:	Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations**IATA-DGR**

UN/ID No.	:	UN 1993
Proper shipping name	:	Flammable liquid, n.o.s. (ALIPHATIC PETROLEUM NAPHTHA)
Class	:	3
Packing group	:	II
Labels	:	3
Packing instruction (cargo aircraft)	:	364
Packing instruction (passenger aircraft)	:	353

IMDG-Code

UN number	:	UN 1993
Proper shipping name	:	FLAMMABLE LIQUID, N.O.S. (ALIPHATIC PETROLEUM NAPHTHA)
Class	:	3
Packing group	:	II
Labels	:	3
EmS Code	:	F-E, <u>S-E</u>
Marine pollutant	:	yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

UN/ID/NA number	:	UN 1993
Proper shipping name	:	Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM NAPHTHA)
Class	:	3
Packing group	:	II
Labels	:	3
ERG Code	:	128

SAFETY DATA SHEET



Car Brite™ HIGH GLOSS DRESSING CL High Gloss Tire Dressing

Version 1.2 Revision Date: 05/05/2018 SDS Number: 600000000189 Date of last issue: 05/02/2017
Date of first issue: 05/23/2016

Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
TOLUENE	108-88-3	1000	1000 (U220)
ETHYL ACETATE	141-78-6	5000	5000 (U112)
BENZENE	71-43-2	10	10 (U019)
ETHYL BENZENE	100-41-4	1000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Aspiration hazard

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

California Prop. 65

WARNING! This product contains a chemical known to the State of California to cause cancer.
WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SAFETY DATA SHEET




Car Brite™ HIGH GLOSS DRESSING CL High Gloss Tire Dressing

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2017
1.2	05/05/2018	600000000189	Date of first issue: 05/23/2016

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

Revision Date : 05/05/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN