

# SAFETY DATA SHEET



## Car Brite™ HYPERSHINE™ High Gloss Tire Dressing

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 09/19/2017  |
| 1.4     | 05/05/2018     | 600000000187 | Date of first issue: 05/23/2016 |

### SECTION 1. IDENTIFICATION

Product name : HYPERSHINE PL 5 GA

Product code : 780729

#### Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : Dallas TX 19162

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

#### Recommended use of the chemical and restrictions on use

Recommended use : POLISH

Restrictions on use : Use only outdoors or in a well-ventilated area.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 2

Aspiration hazard : Category 1

#### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.

Precautionary statements : **Prevention:**  
P210 Keep away from heat/sparks/open flames/hot surfaces.  
No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use only non-sparking tools.

**Car Brite™ HYPERSHINE™ High Gloss Tire Dressing**

Version 1.4      Revision Date: 05/05/2018      SDS Number: 600000000187      Date of last issue: 09/19/2017  
Date of first issue: 05/23/2016

P243 Take precautionary measures against static discharge.  
P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

Static-accumulating flammable liquid.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components**

| Chemical name                                | CAS-No.    | Concentration (% w/w) |
|----------------------------------------------|------------|-----------------------|
| SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC | 64742-89-8 | >= 70 - < 90          |
| n-HEPTANE                                    | 142-82-5   | >= 1 - < 5            |
| ETHYLENE GLYCOL MONOBUTYL ETHER              | 111-76-2   | >= 1 - < 5            |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If on clothes, remove clothes.  
Remove contaminated clothing. If irritation develops, get medical attention.  
If on skin, rinse well with water.  
Wash contaminated clothing before re-use.

# SAFETY DATA SHEET



## Car Brite™ HYPERSHINE™ High Gloss Tire Dressing

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 09/19/2017  |
| 1.4     | 05/05/2018     | 600000000187 | Date of first issue: 05/23/2016 |

- If skin irritation persists, call a physician.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.
- If swallowed : Obtain medical attention.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical  
Alcohol-resistant foam
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides  
Silicon oxides
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Do not use a solid water stream as it may scatter and spread fire.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Ensure adequate ventilation.  
Avoid breathing dust.

# Car Brite™ HYPERSHINE™ High Gloss Tire Dressing

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 09/19/2017  |
| 1.4     | 05/05/2018     | 600000000187 | Date of first issue: 05/23/2016 |

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
Evacuate personnel to safe areas.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.  
Prevent product from entering drains.  
Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

## SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.  
Keep away from open flames, hot surfaces and sources of ignition.  
Use only explosion-proof equipment.  
Do not spray on a naked flame or any incandescent material.

Advice on safe handling : Open drum carefully as content may be under pressure.  
Avoid formation of aerosol.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Do not breathe vapours/dust.  
Do not smoke.  
Take precautionary measures against static discharges.  
Avoid contact with skin and eyes.  
Dispose of rinse water in accordance with local and national regulations.  
Container hazardous when empty.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
No smoking.

Further information on storage : No decomposition if stored and applied as directed.

## SAFETY DATA SHEET


**Car Brite™ HYPERSHINE™ High Gloss Tire Dressing**

Version 1.4      Revision Date: 05/05/2018      SDS Number: 600000000187      Date of last issue: 09/19/2017  
 Date of first issue: 05/23/2016

age stability

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Components with workplace control parameters**

| Components                      | CAS-No.  | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis     |
|---------------------------------|----------|-------------------------------|------------------------------------------------|-----------|
| n-HEPTANE                       | 142-82-5 | TWA                           | 85 ppm<br>350 mg/m <sup>3</sup>                | NIOSH REL |
|                                 |          | C                             | 440 ppm<br>1,800 mg/m <sup>3</sup>             | NIOSH REL |
|                                 |          | TWA                           | 500 ppm<br>2,000 mg/m <sup>3</sup>             | OSHA Z-1  |
|                                 |          | TWA                           | 400 ppm<br>1,600 mg/m <sup>3</sup>             | OSHA P0   |
|                                 |          | STEL                          | 500 ppm<br>2,000 mg/m <sup>3</sup>             | OSHA P0   |
| ETHYLENE GLYCOL MONOBUTYL ETHER | 111-76-2 | TWA                           | 20 ppm                                         | ACGIH     |
|                                 |          | TWA                           | 5 ppm<br>24 mg/m <sup>3</sup>                  | NIOSH REL |
|                                 |          | TWA                           | 50 ppm<br>240 mg/m <sup>3</sup>                | OSHA Z-1  |
|                                 |          | TWA                           | 25 ppm<br>120 mg/m <sup>3</sup>                | OSHA P0   |

**Hazardous components without workplace control parameters**

| Components                                   | CAS-No.    |
|----------------------------------------------|------------|
| SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC | 64742-89-8 |

**Biological occupational exposure limits**

| Components                      | CAS-No.  | Control parameters      | Biological specimen | Sampling time                                            | Permissible concentration | Basis     |
|---------------------------------|----------|-------------------------|---------------------|----------------------------------------------------------|---------------------------|-----------|
| ETHYLENE GLYCOL MONOBUTYL ETHER | 111-76-2 | Butoxyacetic acid (BAA) | Urine               | End of shift (As soon as possible after exposure ceases) | 200 mg/g Creatinine       | ACGIH BEI |

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Personal protective equipment**

Hand protection

**Car Brite™ HYPERSHINE™ High Gloss Tire Dressing**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 09/19/2017  |
| 1.4     | 05/05/2018     | 600000000187 | Date of first issue: 05/23/2016 |

- |                          |                                                                                                                                                                                                             |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Remarks                  | : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves.                                 |
| Eye protection           | : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.                                                                          |
| Skin and body protection | : Choose body protection according to the amount and concentration of the dangerous substance at the work place.<br>Wear as appropriate:<br>Impervious clothing<br>Flame-resistant clothing<br>Safety shoes |
| Hygiene measures         | : Handle in accordance with good industrial hygiene and safety practice.<br>When using do not smoke.<br>When using do not eat or drink.                                                                     |

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- |                                                  |                                             |
|--------------------------------------------------|---------------------------------------------|
| Appearance                                       | : liquid                                    |
| Colour                                           | : blue                                      |
| Odour                                            | : No data available                         |
| pH                                               | : No data available                         |
|                                                  | : No data available                         |
| Boiling point/boiling range                      | : 95 °C<br>The value is calculated          |
| Flash point                                      | : -3.9 °C<br>Method: closed cup             |
| Evaporation rate                                 | : No data available                         |
| Flammability (liquids)                           | : Static-accumulating flammable liquid.     |
| Self-ignition                                    | : No data available                         |
| Upper explosion limit / Upper flammability limit | : 10.6 %(V)<br>The value is calculated      |
| Lower explosion limit / Lower flammability limit | : 1.1 %(V)<br>The value is calculated       |
| Vapour pressure                                  | : 60 hPa (20 °C)<br>The value is calculated |
| Density                                          | : 0.753 g/cm3                               |

# SAFETY DATA SHEET



## Car Brite™ HYPERSHINE™ High Gloss Tire Dressing

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 09/19/2017  |
| 1.4     | 05/05/2018     | 600000000187 | Date of first issue: 05/23/2016 |

---

|                                        |                     |
|----------------------------------------|---------------------|
| Solubility(ies)                        |                     |
| Water solubility                       | : insoluble         |
| Partition coefficient: n-octanol/water | : No data available |
| Viscosity                              |                     |
| Viscosity, dynamic                     | : No data available |
| Viscosity, kinematic                   | : No data available |
| Oxidizing properties                   | : No data available |

---

### SECTION 10. STABILITY AND REACTIVITY

|                                    |                                                                                                                                 |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Reactivity                         | : No decomposition if stored and applied as directed.                                                                           |
| Chemical stability                 | : Stable under normal conditions.                                                                                               |
|                                    | No decomposition if stored and applied as directed.                                                                             |
| Possibility of hazardous reactions | : No decomposition if stored and applied as directed.<br>Vapours may form explosive mixture with air.                           |
| Conditions to avoid                | : Heat, flames and sparks.                                                                                                      |
| Incompatible materials             | : Acids<br>Aluminium<br>Amines<br>Ammonia<br>Bases<br>chlorates<br>Chlorine<br>salts of strong bases<br>Strong oxidizing agents |
| Hazardous decomposition products   | : Carbon oxides<br>Silicon oxides                                                                                               |

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Eye contact  
Ingestion

#### Acute toxicity

Not classified based on available information.

#### **Product:**

|                     |                                          |
|---------------------|------------------------------------------|
| Acute oral toxicity | : Acute toxicity estimate: > 5,000 mg/kg |
|---------------------|------------------------------------------|

**Car Brite™ HYPERSHINE™ High Gloss Tire Dressing**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 09/19/2017  |
| 1.4     | 05/05/2018     | 600000000187 | Date of first issue: 05/23/2016 |

---

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 200 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

**Components:****SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:**

Acute oral toxicity : LD50 (Rat): > 8,000 mg/kg

**n-HEPTANE:**

Acute oral toxicity : LD50 (Rat): Expected > 5,000 mg/kg  
Remarks: Information given is based on data obtained from similar substances.

Acute inhalation toxicity : LC50 (Rat, male and female): > 29.29 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): Expected > 2,000 mg/kg  
Assessment: No adverse effect has been observed in acute dermal toxicity tests.  
Remarks: Information given is based on data obtained from similar substances.

**ETHYLENE GLYCOL MONOBUTYL ETHER:**

Acute oral toxicity : LD50 (Guinea pig): 1,200 mg/kg

Acute inhalation toxicity : LC50 (Guinea pig): > 633 ppm  
Exposure time: 1 h  
Test atmosphere: dust/mist  
Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 (Guinea pig): > 2,000 mg/kg  
Assessment: The component/mixture is moderately toxic after single contact with skin.

**Skin corrosion/irritation**

Not classified based on available information.

**Product:**

Result: Repeated exposure may cause skin dryness or cracking.

# SAFETY DATA SHEET



## Car Brite™ HYPERSHINE™ High Gloss Tire Dressing

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 09/19/2017  |
| 1.4     | 05/05/2018     | 600000000187 | Date of first issue: 05/23/2016 |

---

Remarks: May irritate skin.

### **Components:**

#### **SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:**

Result: Possibly irritating to skin

#### **n-HEPTANE:**

Result: Irritating to skin.

#### **ETHYLENE GLYCOL MONOBUTYL ETHER:**

Result: Irritating to skin.

#### **Serious eye damage/eye irritation**

Not classified based on available information.

### **Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

### **Components:**

#### **SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:**

Result: Possibly irritating to eyes

#### **n-HEPTANE:**

Result: Possibly irritating to eyes

#### **ETHYLENE GLYCOL MONOBUTYL ETHER:**

Result: Irritating to eyes.

Assessment: Irritating to eyes.

#### **Respiratory or skin sensitisation**

##### **Skin sensitisation**

Not classified based on available information.

##### **Respiratory sensitisation**

Not classified based on available information.

### **Components:**

#### **n-HEPTANE:**

Test Type: Maximisation Test

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

Remarks: Information given is based on data obtained from similar substances.

#### **Germ cell mutagenicity**

Not classified based on available information.

# SAFETY DATA SHEET



## Car Brite™ HYPERSHINE™ High Gloss Tire Dressing

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 09/19/2017  |
| 1.4     | 05/05/2018     | 600000000187 | Date of first issue: 05/23/2016 |

---

### **Components:**

#### **n-HEPTANE:**

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects

#### **ETHYLENE GLYCOL MONOBUTYL ETHER:**

Genotoxicity in vitro : Test Type: Ames test  
Test system: Salmonella typhimurium  
Metabolic activation: with and without metabolic activation  
Result: negative

### **Carcinogenicity**

Not classified based on available information.

#### **IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

#### **OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### **Reproductive toxicity**

Not classified based on available information.

#### **STOT - single exposure**

Not classified based on available information.

### **Components:**

#### **n-HEPTANE:**

Assessment: May cause drowsiness or dizziness.

#### **STOT - repeated exposure**

Not classified based on available information.

#### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

### **Components:**

#### **SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:**

May be fatal if swallowed and enters airways.

#### **n-HEPTANE:**

May be fatal if swallowed and enters airways.

# SAFETY DATA SHEET



## Car Brite™ HYPERSHINE™ High Gloss Tire Dressing

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 09/19/2017  |
| 1.4     | 05/05/2018     | 600000000187 | Date of first issue: 05/23/2016 |

### Further information

#### Product:

Remarks: No data available

## SECTION 12. ECOLOGICAL INFORMATION

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

|                        |   |                                                                                                                                                          |
|------------------------|---|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Waste from residues    | : | Dispose of in accordance with all applicable local, state and federal regulations.                                                                       |
| Contaminated packaging | : | Empty remaining contents.<br>Dispose of as unused product.<br>Do not re-use empty containers.<br>Do not burn, or use a cutting torch on, the empty drum. |

## SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

### International Regulations

#### **IATA-DGR**

|                                          |   |                                                           |
|------------------------------------------|---|-----------------------------------------------------------|
| UN/ID No.                                | : | UN 1993                                                   |
| Proper shipping name                     | : | Flammable liquid, n.o.s.<br>(ALIPHATIC PETROLEUM NAPHTHA) |
| Class                                    | : | 3                                                         |
| Packing group                            | : | II                                                        |
| Labels                                   | : | 3                                                         |
| Packing instruction (cargo aircraft)     | : | 364                                                       |
| Packing instruction (passenger aircraft) | : | 353                                                       |

#### **IMDG-Code**

|                      |   |                                                           |
|----------------------|---|-----------------------------------------------------------|
| UN number            | : | UN 1993                                                   |
| Proper shipping name | : | FLAMMABLE LIQUID, N.O.S.<br>(ALIPHATIC PETROLEUM NAPHTHA) |
| Class                | : | 3                                                         |
| Packing group        | : | II                                                        |
| Labels               | : | 3                                                         |
| EmS Code             | : | F-E, <u>S-E</u>                                           |
| Marine pollutant     | : | no                                                        |

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

# SAFETY DATA SHEET



## Car Brite™ HYPERSHINE™ High Gloss Tire Dressing

Version 1.4      Revision Date: 05/05/2018      SDS Number: 600000000187      Date of last issue: 09/19/2017  
Date of first issue: 05/23/2016

### 49 CFR

UN/ID/NA number : UN 1993  
Proper shipping name : Flammable liquids, n.o.s.  
(ALIPHATIC PETROLEUM NAPHTHA)  
Class : 3  
Packing group : II  
Labels : 3  
ERG Code : 128  
Marine pollutant : no

## SECTION 15. REGULATORY INFORMATION

### EPCRA - Emergency Planning and Community Right-to-Know Act

#### CERCLA Reportable Quantity

| Components    | CAS-No.  | Component RQ (lbs) | Calculated product RQ (lbs) |
|---------------|----------|--------------------|-----------------------------|
| ETHYL ACETATE | 141-78-6 | 5000               | 5000 (U112)                 |
| TOLUENE       | 108-88-3 | 1000               | 1000 (U220)                 |
| BENZENE       | 71-43-2  | 10                 | 10 (U019)                   |
| ETHYL BENZENE | 100-41-4 | 1000               | *                           |

\*: Calculated RQ exceeds reasonably attainable upper limit.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Aspiration hazard

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### US State Regulations

#### California Prop. 65

WARNING! This product contains a chemical known to the State of California to cause cancer.  
WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

# SAFETY DATA SHEET




## Car Brite™ HYPERSHINE™ High Gloss Tire Dressing

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 09/19/2017  |
| 1.4     | 05/05/2018     | 600000000187 | Date of first issue: 05/23/2016 |

### SECTION 16. OTHER INFORMATION

#### Further information

#### NFPA:



Special hazard.

Revision Date : 05/05/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN