

SAFETY DATA SHEET



Car Brite™ METAL BRITE Wheel Polish

Version	Revision Date:	SDS Number:	Date of last issue:
1.1	05/03/2018	600000000672	05/23/2016
			Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : METAL BRITE 32 FOZ UN

Product code : CBO1B050-02

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : Dallas TX 19162

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Recommended use of the chemical and restrictions on use

Recommended use : POLISH

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 4

Carcinogenicity : Category 1A

Specific target organ toxicity
- repeated exposure (Inhalation)
: Category 1 (Kidney, Respiratory system)

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H227 Combustible liquid.
H350 May cause cancer.
H372 Causes damage to organs (Kidney, Respiratory system)
through prolonged or repeated exposure if inhaled.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read
and understood.

Car Brite™ METAL BRITE Wheel Polish

Version	Revision Date:	SDS Number:	Date of last issue:
1.1	05/03/2018	600000000672	05/23/2016
			Date of first issue: 05/23/2016

P210 Keep away from heat/sparks/open flames/hot surfaces.
No smoking.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/ protective clothing/ eye protection/
face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/
attention.
P370 + P378 In case of fire: Use dry sand, dry chemical or alco-
hol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-
posal plant.

Other hazards

Static-accumulating flammable liquid.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	>= 10 - < 20
QUARTZ / SAND	14808-60-7	>= 5 - < 10
ALUMINUM OXIDE (AL ₂ O ₃)	1344-28-1	>= 5 - < 10
GLYCERIN	56-81-5	>= 1 - < 5
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	>= 1 - < 5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : Move to fresh air.
IF INHALED: Call a POISON CENTER/ doctor if you feel un-
well.
If unconscious, place in recovery position and seek medical
advice.
Keep patient warm and at rest.
If symptoms persist, call a physician.

SAFETY DATA SHEET



Car Brite™ METAL BRITE Wheel Polish

Version	Revision Date:	SDS Number:	Date of last issue:
1.1	05/03/2018	600000000672	05/23/2016
			Date of first issue: 05/23/2016

- | | |
|---|---|
| In case of skin contact | : If on clothes, remove clothes.
Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
If skin irritation persists, call a physician. |
| In case of eye contact | : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing. |
| If swallowed | : Obtain medical attention.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician. |
| Most important symptoms and effects, both acute and delayed | : May cause cancer.
Causes damage to organs through prolonged or repeated exposure if inhaled. |

SECTION 5. FIREFIGHTING MEASURES

- | | |
|---|--|
| Suitable extinguishing media | : Water spray
Carbon dioxide (CO2) |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during fire-fighting | : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.
Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : Carbon oxides
Silicon oxides |
| Specific extinguishing methods | : Product is compatible with standard fire-fighting agents. |
| Further information | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers. |
| Special protective equipment for firefighters | : In the event of fire, wear self-contained breathing apparatus. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|----------------------------------|--------------------------------------|
| Personal precautions, protection | : Use personal protective equipment. |
|----------------------------------|--------------------------------------|

Car Brite™ METAL BRITE Wheel Polish

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	05/03/2018	600000000672	Date of first issue: 05/23/2016

- | | | |
|---|---|--|
| tive equipment and emergency procedures | : | Remove all sources of ignition.
Ensure adequate ventilation.
Avoid breathing dust.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. |
| Environmental precautions | : | Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods and materials for containment and cleaning up | : | Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal. |

SECTION 7. HANDLING AND STORAGE

- | | | |
|---|---|--|
| Advice on protection against fire and explosion | : | Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.
Keep away from open flames, hot surfaces and sources of ignition.
Do not spray on a naked flame or any incandescent material. |
| Advice on safe handling | : | Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Avoid contact with skin and eyes.
Dispose of rinse water in accordance with local and national regulations.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8. |
| Conditions for safe storage | : | Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
No smoking. |
| Further information on storage stability | : | No decomposition if stored and applied as directed. |

SAFETY DATA SHEET



Car Brite™ METAL BRITE Wheel Polish

Version 1.1 Revision Date: 05/03/2018 SDS Number: 600000000672 Date of last issue: 05/23/2016
Date of first issue: 05/23/2016

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
QUARTZ / SAND	14808-60-7	TWA (respirable)	10 mg/m3 / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable fraction)	0.025 mg/m3 (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL
ALUMINUM OXIDE (AL ₂ O ₃)	1344-28-1	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
GLYCERIN	56-81-5	TWA (mist, respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (mist, total dust)	15 mg/m3	OSHA Z-1

Hazardous components without workplace control parameters

Components	CAS-No.
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Car Brite™ METAL BRITE Wheel Polish

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	05/03/2018	600000000672	Date of first issue: 05/23/2016

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear as appropriate:
Impervious clothing
Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not smoke.
When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous

Colour : violet

Odour : ammoniacal

pH : 8.5

Melting point/freezing point : 20 °C

Boiling point/boiling range : > 150 °F
(1013.25 hPa)

Flash point : 80 °C
The value is calculated

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Flammability (liquids) : Static-accumulating flammable liquid.

Self-ignition : 228.9 °C

Upper explosion limit / Upper flammability limit : 25 %(V)
The value is calculated

Lower explosion limit / Lower : 0.7 %(V)

SAFETY DATA SHEET



Car Brite™ METAL BRITE Wheel Polish

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	05/03/2018	600000000672	Date of first issue: 05/23/2016

flammability limit	The value is calculated
Vapour pressure	: 1,006.7 hPa (26.67 °C) The value is calculated
Density	: 1.051 g/cm3
Solubility(ies)	
Water solubility	: partly soluble
Partition coefficient: n-octanol/water	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 100 mm2/s (40 °C)
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Acids Bases halogens Ethylene oxide Reducing agents Strong bases Strong oxidizing agents
Hazardous decomposition products	: Carbon oxides Silicon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Eye contact
Skin contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Car Brite™ METAL BRITE Wheel Polish

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	05/03/2018	600000000672	Date of first issue: 05/23/2016

Acute inhalation toxicity : Acute toxicity estimate: > 30000 ppm
Exposure time: 4 h
Test atmosphere: gas
Method: Calculation method

Remarks: Prolonged or repeated breathing of dust may result in progressive and permanent lung disease (fibrosis) which may cause death from respiratory and/or heart failure. Symptoms include coughing and difficult breathing which becomes worse with physical activity.
Another form of fibrosis, acute silicosis, can occur with exposures to very high concentrations of respirable silica over shorter periods of time, sometimes as short as a few months. Symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis is fatal.

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:**GLYCERIN:**

Acute oral toxicity : LD50 (Rat): 12,600 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 570 mg/m3
Exposure time: 1 h
Test atmosphere: vapour
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 10 g/kg

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May irritate skin.

Car Brite™ METAL BRITE Wheel Polish

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	05/03/2018	600000000672	Date of first issue: 05/23/2016

Components:**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

Result: Repeated exposure may cause skin dryness or cracking.

QUARTZ / SAND:

Result: Possibly irritating to skin

ALUMINUM OXIDE (AL₂O₃):

Result: Possibly irritating to skin

GLYCERIN:

Assessment: No skin irritation

Result: No skin irritation

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Result: Irritating to skin.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:**QUARTZ / SAND:**

Result: Possibly irritating to eyes

ALUMINUM OXIDE (AL₂O₃):

Result: Possibly irritating to eyes

GLYCERIN:

Result: Possibly irritating to eyes

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Result: Possibly irritating to eyes

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Car Brite™ METAL BRITE Wheel Polish

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	05/03/2018	600000000672	Date of first issue: 05/23/2016

Carcinogenicity

May cause cancer.

Components:**QUARTZ / SAND:**

Carcinogenicity - Assessment : Human carcinogen.

IARC

Group 1: Carcinogenic to humans

QUARTZ / SAND 14808-60-7

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

Known to be human carcinogen

QUARTZ / SAND 14808-60-7

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

Components:**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Causes damage to organs (Kidney, Respiratory system) through prolonged or repeated exposure if inhaled.

Components:**QUARTZ / SAND:**

Exposure routes: inhalation (dust/mist/fume)

Target Organs: Kidney, Respiratory system

Assessment: Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Components:**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

May be fatal if swallowed and enters airways.

SAFETY DATA SHEET



Car Brite™ METAL BRITE Wheel Polish

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	05/03/2018	600000000672	Date of first issue: 05/23/2016

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

SAFETY DATA SHEET



Car Brite™ METAL BRITE Wheel Polish

Version 1.1 Revision Date: 05/03/2018 SDS Number: 600000000672 Date of last issue: 05/23/2016
Date of first issue: 05/23/2016

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
METHANOL	67-56-1	5000	5000 (U154)
AMMONIA	7664-41-7	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
AMMONIA	7664-41-7	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Hazard not otherwise classified (physical hazards)
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations


California Prop. 65

WARNING! This product contains a chemical known to the State of California to cause cancer.
WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

Revision Date : 05/03/2018

SAFETY DATA SHEET



Car Brite™ METAL BRITE Wheel Polish

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	05/03/2018	600000000672	Date of first issue: 05/23/2016

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN