

SAFETY DATA SHEET



Car Brite™ NANOWAX™ Liquid Wax

Version	Revision Date:	SDS Number:	Date of last issue:
1.1	05/03/2018	600000000609	05/23/2016
			Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : NANOWAX HIGH GLOSS WAX 4/1 GA

Product code : CBOOA036Q03

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : Dallas TX 19162

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Recommended use of the chemical and restrictions on use

Recommended use : WAX

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 3

Specific target organ toxicity : Category 3 (Central nervous system)
- single exposure

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**
P210 Keep away from heat/sparks/open flames/hot surfaces.
No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equip-
ment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.

Car Brite™ NANOWAX™ Liquid Wax

Version	Revision Date:	SDS Number:	Date of last issue:
1.1	05/03/2018	600000000609	05/23/2016
			Date of first issue: 05/23/2016

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	>= 20 - < 30
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	64742-48-9	>= 10 - < 20
ALUMINUM OXIDE (AL ₂ O ₃)	1344-28-1	>= 1 - < 5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Move to fresh air. Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: If on clothes, remove clothes. If on skin, rinse well with water.

SAFETY DATA SHEET



Car Brite™ NANOWAX™ Liquid Wax

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	05/03/2018	600000000609	Date of first issue: 05/23/2016

- | | | |
|---|---|--|
| In case of eye contact | : | Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing. |
| If swallowed | : | Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician. |
| Most important symptoms and effects, both acute and delayed | : | May cause drowsiness or dizziness. |

SECTION 5. FIREFIGHTING MEASURES

- | | | |
|---|---|--|
| Suitable extinguishing media | : | Water spray
Carbon dioxide (CO2)
Dry chemical
Alcohol-resistant foam |
| Unsuitable extinguishing media | : | High volume water jet |
| Specific hazards during fire-fighting | : | Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : | Carbon oxides
Silicon oxides |
| Specific extinguishing methods | : | Product is compatible with standard fire-fighting agents. |
| Further information | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers. |
| Special protective equipment for firefighters | : | In the event of fire, wear self-contained breathing apparatus. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | | |
|---|---|---|
| Personal precautions, protective equipment and emergency procedures | : | Remove all sources of ignition.
Avoid breathing dust.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Evacuate personnel to safe areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. |
| Environmental precautions | : | Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform |

Car Brite™ NANOWAX™ Liquid Wax

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	05/03/2018	600000000609	Date of first issue: 05/23/2016

respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.
Keep away from open flames, hot surfaces and sources of ignition.
Use only explosion-proof equipment.
Do not spray on a naked flame or any incandescent material.

Advice on safe handling : Open drum carefully as content may be under pressure.
Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Take precautionary measures against static discharges.
Dispose of rinse water in accordance with local and national regulations.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
No smoking.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA	200 mg/m3	ACGIH

SAFETY DATA SHEET



Car Brite™ NANOWAX™ Liquid Wax

Version 1.1 Revision Date: 05/03/2018 SDS Number: 600000000609 Date of last issue: 05/23/2016
Date of first issue: 05/23/2016

			(total hydrocarbon vapor)	
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
ALUMINUM OXIDE (AL2O3)	1344-28-1	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0

Hazardous components without workplace control parameters

Components	CAS-No.
Hydrocarbons, C10-C12, iso-alkanes, <2% aromatics	64742-48-9

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear as appropriate:
Impervious clothing
Flame-resistant clothing
Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : beige

SAFETY DATA SHEET



Car Brite™ NANOWAX™ Liquid Wax

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	05/03/2018	600000000609	Date of first issue: 05/23/2016

Odour	:	like fruit
pH	:	No data available
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	40 °C The value is calculated
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	6 %(V) The value is calculated
Lower explosion limit / Lower flammability limit	:	0.7 %(V) The value is calculated
Vapour pressure	:	< 2 mmHg (20 °C) The value is calculated
Density	:	0.907 g/cm3
Solubility(ies)	:	
Water solubility	:	partly soluble
Partition coefficient: n-octanol/water	:	No data available
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 100 mm2/s (40 °C)
Oxidizing properties	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Acids halogens Ethylene oxide Oxidizing agents

Car Brite™ NANOWAX™ Liquid Wax

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	05/03/2018	600000000609	Date of first issue: 05/23/2016

Strong reducing agents

Hazardous decomposition products : Carbon oxides
Silicon oxides

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Eye contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:**Hydrocarbons, C10-C12, isoalkanes, <2% aromatics:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2240 ppm
Exposure time: 4 h
Test atmosphere: vapour
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Skin corrosion/irritation

Not classified based on available information.

Components:**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

Result: Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10-C12, isoalkanes, <2% aromatics:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Result: Repeated exposure may cause skin dryness or cracking.

ALUMINUM OXIDE (AL₂O₃):

Result: Possibly irritating to skin

Car Brite™ NANOWAX™ Liquid Wax

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	05/03/2018	600000000609	Date of first issue: 05/23/2016

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:**Hydrocarbons, C10-C12, isoalkanes, <2% aromatics:**

Species: Rabbit

Result: No eye irritation

ALUMINUM OXIDE (AL₂O₃):

Result: Possibly irritating to eyes

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

SAFETY DATA SHEET



Car Brite™ NANOWAX™ Liquid Wax

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	05/03/2018	600000000609	Date of first issue: 05/23/2016

Aspiration toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

May be fatal if swallowed and enters airways.

Hydrocarbons, C10-C12, isoalkanes, <2% aromatics:

May be fatal if swallowed and enters airways.

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12. ECOLOGICAL INFORMATION

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- | | | |
|------------------------|---|--|
| Waste from residues | : | Dispose of in accordance with all applicable local, state and federal regulations. |
| Contaminated packaging | : | Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum. |

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

- | | | |
|--------------------------------------|---|--|
| UN/ID No. | : | UN 1993 |
| Proper shipping name | : | Flammable liquid, n.o.s.
(SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC) |
| Class | : | 3 |
| Packing group | : | III |
| Labels | : | 3 |
| Packing instruction (cargo aircraft) | : | 366 |
| Packing instruction | : | 355 |

SAFETY DATA SHEET



Car Brite™ NANOWAX™ Liquid Wax

Version 1.1 Revision Date: 05/03/2018 SDS Number: 600000000609 Date of last issue: 05/23/2016
Date of first issue: 05/23/2016

(passenger aircraft)

IMDG-Code

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC)
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 1993
Proper shipping name : Flammable liquids, n.o.s.
(SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC)
Class : 3
Packing group : III
Labels : 3
ERG Code : 128
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
1,4-DIOXANE	123-91-1	100	100 (U108)
ACETIC ACID GLACIAL	64-19-7	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Specific target organ toxicity (single or repeated exposure)

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

California Prop. 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

SAFETY DATA SHEET




Car Brite™ NANOWAX™ Liquid Wax

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	05/03/2018	600000000609	Date of first issue: 05/23/2016

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Revision Date : 05/03/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN