

Car Brite™ REVIVE™ Ready-To-Use Bumper & Trim Dressing

Version	Revision Date:	SDS Number:	Date of last issue: 04/24/2017
1.2	04/29/2018	600000000720	Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : REVIVE TRIM TREATMENT 12/32 FOZ

Product code : CBOOC010A02

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : Dallas TX 19162

Recommended use of the chemical and restrictions on use

Recommended use : LEATHER CARE

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200**

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H361f Suspected of damaging fertility.Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.

Car Brite™ REVIVE™ Ready-To-Use Bumper & Trim Dressing

Version	Revision Date:	SDS Number:	Date of last issue: 04/24/2017
1.2	04/29/2018	600000000720	Date of first issue: 05/23/2016

P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

Static-accumulating flammable liquid.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	>= 10 - < 20
MORPHOLINE	110-91-8	>= 1 - < 3
SILOXANES AND SILICONES, DI-METHYL, [[3-[(2-AMIN	67923-07-3	>= 1 - < 5
OCTAMETHYLCYCLOTETRA-SILOXANE	556-67-2	>= 0.1 - < 1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.

SAFETY DATA SHEET



Car Brite™ REVIVE™ Ready-To-Use Bumper & Trim Dressing

Version	Revision Date:	SDS Number:	Date of last issue: 04/24/2017
1.2	04/29/2018	600000000720	Date of first issue: 05/23/2016

- Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on clothes, remove clothes.
Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
If skin irritation persists, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
Causes serious eye irritation.
Suspected of damaging fertility.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Carbon dioxide (CO2)
Dry chemical
Alcohol-resistant foam
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
Silicon oxides
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.
- Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Car Brite™ REVIVE™ Ready-To-Use Bumper & Trim Dressing

Version	Revision Date:	SDS Number:	Date of last issue: 04/24/2017
1.2	04/29/2018	600000000720	Date of first issue: 05/23/2016

for firefighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Avoid breathing dust.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Evacuate personnel to safe areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.
Keep away from open flames, hot surfaces and sources of ignition.
Use only explosion-proof equipment.
Do not spray on a naked flame or any incandescent material.
- Advice on safe handling : Open drum carefully as content may be under pressure.
Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Take precautionary measures against static discharges.
Avoid contact with skin and eyes.
Dispose of rinse water in accordance with local and national regulations.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

Car Brite™ REVIVE™ Ready-To-Use Bumper & Trim Dressing

Version 1.2 Revision Date: 04/29/2018 SDS Number: 600000000720 Date of last issue: 04/24/2017
Date of first issue: 05/23/2016

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
No smoking.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
MORPHOLINE	110-91-8	TWA	20 ppm	ACGIH
		TWA	20 ppm 70 mg/m ³	NIOSH REL
		ST	30 ppm 105 mg/m ³	NIOSH REL
		TWA	20 ppm 70 mg/m ³	OSHA Z-1
		TWA	20 ppm 70 mg/m ³	OSHA P0
		STEL	30 ppm 105 mg/m ³	OSHA P0
OCTAMETHYLCYCLOTETRA SILOXANE	556-67-2	TWA	10 ppm	US WEEL

Hazardous components without workplace control parameters

Components	CAS-No.
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8
SILOXANES AND SILICONES, DI-METHYL, [[[3-[(2-AMIN	67923-07-3

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.

Eye protection : Wear chemical splash goggles when there is the potential for

Car Brite™ REVIVE™ Ready-To-Use Bumper & Trim Dressing

Version	Revision Date:	SDS Number:	Date of last issue: 04/24/2017
1.2	04/29/2018	600000000720	Date of first issue: 05/23/2016

- exposure of the eyes to liquid, vapor or mist.
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear as appropriate:
Impervious clothing
Flame-resistant clothing
Safety shoes
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not smoke.
When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : viscous
- Colour : white
- Odour : solvent-like
- pH : 8.5
- Melting point/freezing point : No data available
- Boiling point/boiling range : 65 °C
(1,013 hPa)
The value is calculated
- Flash point : 50.56 °C
Method: Tag closed cup
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Flammability (liquids) : Static-accumulating flammable liquid.
- Self-ignition : No data available
- Upper explosion limit / Upper flammability limit : 11.2 %(V)
The value is calculated
- Lower explosion limit / Lower flammability limit : 1 %(V)
The value is calculated
- Vapour pressure : 23.33 hPa (20 °C)
The value is calculated
- Density : 0.923 g/cm3
- Solubility(ies)
Water solubility : No data available

SAFETY DATA SHEET



Car Brite™ REVIVE™ Ready-To-Use Bumper & Trim Dressing

Version	Revision Date:	SDS Number:	Date of last issue: 04/24/2017
1.2	04/29/2018	600000000720	Date of first issue: 05/23/2016

Partition coefficient: n-octanol/water	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 100 mm ² /s (40 °C)
Oxidizing properties	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Acids acrylates Alcohols Aldehydes Bases glycols Halogenated compounds isocyanates Ketones Metals Nitrous acid and other nitrosating agents organic anhydrides Reducing agents Strong oxidizing agents
Hazardous decomposition products	:	Carbon oxides Silicon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Eye contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
---------------------	---	--

Car Brite™ REVIVE™ Ready-To-Use Bumper & Trim Dressing

Version	Revision Date:	SDS Number:	Date of last issue: 04/24/2017
1.2	04/29/2018	600000000720	Date of first issue: 05/23/2016

Acute inhalation toxicity : Acute toxicity estimate: > 200 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

MORPHOLINE:

Acute oral toxicity : LD50 (Rat): ca. 1,900 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : Assessment: The component/mixture is toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): ca. 500 mg/kg

OCTAMETHYLCYCLOTETRAILOXANE:

Acute oral toxicity : LD50 (Rat): > 4,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 36 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,400 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Skin corrosion/irritation

Causes skin irritation.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation and/or dermatitis.

Car Brite™ REVIVE™ Ready-To-Use Bumper & Trim Dressing

Version	Revision Date:	SDS Number:	Date of last issue: 04/24/2017
1.2	04/29/2018	600000000720	Date of first issue: 05/23/2016

Components:**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

Result: Irritating to skin.

MORPHOLINE:

Result: Corrosive after 3 minutes or less of exposure

SILOXANES AND SILICONES, DI-METHYL, [[[3-[(2-AMIN:

Assessment: No skin irritation

Result: No skin irritation

OCTAMETHYLCYCLOTETRASIOXANE:

Species: Rabbit

Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

Result: Possibly irritating to eyes

MORPHOLINE:

Result: Irreversible effects on the eye

SILOXANES AND SILICONES, DI-METHYL, [[[3-[(2-AMIN:

Result: Irritating to eyes.

OCTAMETHYLCYCLOTETRASIOXANE:

Species: Rabbit

Result: Possibly irritating to eyes

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:**OCTAMETHYLCYCLOTETRASIOXANE:**

Test Type: Maximisation Test

Car Brite™ REVIVE™ Ready-To-Use Bumper & Trim Dressing

Version	Revision Date:	SDS Number:	Date of last issue: 04/24/2017
1.2	04/29/2018	600000000720	Date of first issue: 05/23/2016

Species: Guinea pig
Assessment: Does not cause skin sensitisation.
Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components:**MORPHOLINE:**

Genotoxicity in vitro : Test Type: unscheduled DNA synthesis assay
Test system: rat hepatocytes
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 482
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Test system: mouse lymphoma cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: positive

OCTAMETHYLCYCLOTETRAISILOXANE:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Suspected of damaging fertility.

Components:**OCTAMETHYLCYCLOTETRAISILOXANE:**

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

STOT - single exposure

Not classified based on available information.

SAFETY DATA SHEET



Car Brite™ REVIVE™ Ready-To-Use Bumper & Trim Dressing

Version	Revision Date:	SDS Number:	Date of last issue: 04/24/2017
1.2	04/29/2018	600000000720	Date of first issue: 05/23/2016

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	:	Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

UN/ID No.	:	UN 1993
Proper shipping name	:	Flammable liquid, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES)
Class	:	3
Packing group	:	III
Labels	:	3
Packing instruction (cargo)	:	366

SAFETY DATA SHEET



Car Brite™ REVIVE™ Ready-To-Use Bumper & Trim Dressing

Version 1.2 Revision Date: 04/29/2018 SDS Number: 600000000720 Date of last issue: 04/24/2017
Date of first issue: 05/23/2016

aircraft)
Packing instruction : 355
(passenger aircraft)

IMDG-Code

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(ALIPHATIC PETROLEUM DISTILLATES)
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 1993
Proper shipping name : Flammable liquids, n.o.s.
(ALIPHATIC PETROLEUM DISTILLATES)
Class : 3
Packing group : III
Labels : 3
ERG Code : 128
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
METHANOL	67-56-1	5000	5000 (U154)

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Hazard not otherwise classified (physical hazards)
Skin corrosion or irritation
Serious eye damage or eye irritation
Reproductive toxicity

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SAFETY DATA SHEET



Car Brite™ REVIVE™ Ready-To-Use Bumper & Trim Dressing

Version	Revision Date:	SDS Number:	Date of last issue: 04/24/2017
1.2	04/29/2018	600000000720	Date of first issue: 05/23/2016

US State Regulations


California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Revision Date : 04/29/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN