

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 04/27/2018
3.0	08/10/2018	1459120-00005	Date of first issue: 02/06/2014

SECTION 1. IDENTIFICATION

Product name : Tire Fitting Lubricant, 5 kg

Product code : 890.1221

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : CANUTEC (24/7): +1 (613) 996-6666 or/ou *666 (cellular/cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Anti-friction agent and lubricant

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Specific target organ systemic toxicity - repeated exposure (Oral) : Category 2 (Kidney)

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H373 May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.

Precautionary Statements : **Prevention:**
P260 Do not breathe mist or vapors.
Response:
P314 Get medical advice/ attention if you feel unwell.

Tire Fitting Lubricant, 5 kg

Version 3.0 Revision Date: 08/10/2018 SDS Number: 1459120-00005 Date of last issue: 04/27/2018
Date of first issue: 02/06/2014

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Stearic acid	57-11-4	≥ 30 - < 60
Sodium stearate	822-16-2	≥ 10 - < 30
Diethylene glycol	111-46-6	≥ 5 - < 10

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : May cause damage to organs through prolonged or repeated exposure if swallowed.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 04/27/2018
3.0	08/10/2018	1459120-00005	Date of first issue: 02/06/2014

Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Metal oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 04/27/2018
3.0	08/10/2018	1459120-00005	Date of first issue: 02/06/2014

CONTROLS/PERSONAL PROTECTION section.

- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Avoid inhalation of vapor or mist.
Do not swallow.
Avoid contact with eyes.
Avoid prolonged or repeated contact with skin.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Stearic acid	57-11-4	TWA (Inhalable fraction)	10 mg/m ³	ACGIH
		TWA (Respirable fraction)	3 mg/m ³	ACGIH
Sodium stearate	822-16-2	TWA	10 mg/m ³	CA AB OEL
		TWA	10 mg/m ³	CA BC OEL
		TWA (Inhalable fraction)	10 mg/m ³	ACGIH
		TWA (Respirable fraction)	3 mg/m ³	ACGIH

- Engineering measures** : Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.
Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m³ - total dust, 5 mg/m³ - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m³ - respirable particles, 10 mg/m³ - inhalable particles.

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 04/27/2018
3.0	08/10/2018	1459120-00005	Date of first issue: 02/06/2014

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapor type

Hand protection
Material : Natural Rubber

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Eye protection : Wear the following personal protective equipment:
Safety glasses
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.
Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.

Skin and body protection : Skin should be washed after contact.

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : white

Odor : mild

Odor Threshold : No data available

pH : ca. 8 (20 °C)
(as an emulsion)

Melting point/freezing point : ca. 50 °C

Initial boiling point and boiling range : No data available

Flash point : ca. 240 °C

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 04/27/2018
3.0	08/10/2018	1459120-00005	Date of first issue: 02/06/2014

Method: DIN 51376

Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	No data available
Density	:	1.06 g/cm ³ (20 °C)
Solubility(ies)		
Water solubility	:	completely miscible
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	ca. 400 °C
Decomposition temperature	:	No data available
Viscosity		
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Can react with strong oxidizing agents.
Conditions to avoid	:	None known.
Incompatible materials	:	Oxidizing agents

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 04/27/2018
3.0	08/10/2018	1459120-00005	Date of first issue: 02/06/2014

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:**Stearic acid:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 2 mg/l
Exposure time: 1 h
Test atmosphere: vapor
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Sodium stearate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Diethylene glycol:

Acute oral toxicity : LD50 (Humans): 1,120 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:**Stearic acid:**

Species : Rabbit
Method : Patch Test 24 Hrs.
Result : No skin irritation

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 04/27/2018
3.0	08/10/2018	1459120-00005	Date of first issue: 02/06/2014

Sodium stearate:

Species	: Rabbit
Result	: No skin irritation

Diethylene glycol:

Species	: Rabbit
Result	: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Stearic acid:**

Species	: Rabbit
Result	: No eye irritation

Sodium stearate:

Species	: Rabbit
Result	: No eye irritation

Diethylene glycol:

Species	: Rabbit
Result	: No eye irritation

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:**Stearic acid:**

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Result	: negative
Remarks	: Based on data from similar materials

Sodium stearate:

Assessment	: Does not cause skin sensitization.
------------	--------------------------------------

Diethylene glycol:

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 04/27/2018
3.0	08/10/2018	1459120-00005	Date of first issue: 02/06/2014

Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Stearic acid:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Sodium stearate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Diethylene glycol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Not classified based on available information.

Components:**Sodium stearate:**

Species : Rat
Application Route : Ingestion
Exposure time : 20 weeks
Result : negative
Remarks : Based on data from similar materials

Diethylene glycol:

Species : Rat

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 04/27/2018
3.0	08/10/2018	1459120-00005	Date of first issue: 02/06/2014

Application Route	: Ingestion
Exposure time	: 104 weeks
Result	: negative

Reproductive toxicity

Not classified based on available information.

Components:**Stearic acid:**

Effects on fertility	: Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 422 Result: negative Remarks: Based on data from similar materials
Effects on fetal development	: Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 422 Result: negative Remarks: Based on data from similar materials

Diethylene glycol:

Effects on fertility	: Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: Ingestion Result: negative
Effects on fetal development	: Test Type: Embryo-fetal development Species: Rat Application Route: Ingestion Method: OECD Test Guideline 414 Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.

Components:**Diethylene glycol:**

Routes of exposure	: Ingestion
Target Organs	: Kidney
Assessment	: Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 04/27/2018
3.0	08/10/2018	1459120-00005	Date of first issue: 02/06/2014

Repeated dose toxicity**Components:****Stearic acid:**

Species	: Rat
NOAEL	: 1,000 mg/kg
Application Route	: Ingestion
Exposure time	: 42 Days
Method	: OECD Test Guideline 422
Remarks	: Based on data from similar materials

Diethylene glycol:

Species	: Rat
NOAEL	: 100 mg/kg
Application Route	: Ingestion
Exposure time	: 225 Days

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Stearic acid:**

Toxicity to fish	: LL50 (Leuciscus idus (Golden orfe)): > 10,000 mg/l Exposure time: 48 h Method: DIN 38412
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 10 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 Remarks: Based on data from similar materials No toxicity at the limit of solubility.
Toxicity to algae	: NOELR (Pseudokirchneriella subcapitata (green algae)): > 10 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials No toxicity at the limit of solubility. EL50 (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials No toxicity at the limit of solubility.
Toxicity to daphnia and other aquatic invertebrates (Chron-	: NOELR (Daphnia magna (Water flea)): > 0.5 mg/l Exposure time: 21 d

Version	Revision Date:	SDS Number:	Date of last issue: 04/27/2018
3.0	08/10/2018	1459120-00005	Date of first issue: 02/06/2014

ic toxicity)		Method: OECD Test Guideline 211 Remarks: Based on data from similar materials No toxicity at the limit of solubility.
Toxicity to microorganisms	:	EC10 (<i>Pseudomonas putida</i>): 883 mg/l Exposure time: 18 h
Sodium stearate:		
Toxicity to fish	:	LC50 (<i>Oryzias latipes</i> (Orange-red killifish)): > 100 mg/l Exposure time: 96 h Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (<i>Daphnia magna</i> (Water flea)): 24 mg/l Exposure time: 48 h Remarks: Based on data from similar materials
Toxicity to algae	:	EC50 (<i>Selenastrum capricornutum</i> (green algae)): 63 mg/l Exposure time: 72 h
Diethylene glycol:		
Toxicity to fish	:	LC50 (<i>Pimephales promelas</i> (fathead minnow)): 75,200 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (<i>Daphnia magna</i> (Water flea)): > 10,000 mg/l Exposure time: 24 h
Toxicity to algae	:	EC50 (<i>Selenastrum capricornutum</i> (green algae)): 6,500 - 13,000 mg/l Exposure time: 96 h Remarks: Based on data from similar materials
Toxicity to fish (Chronic toxicity)	:	NOEC (<i>Pimephales promelas</i> (fathead minnow)): 15,380 mg/l Exposure time: 7 d Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (<i>Daphnia magna</i> (Water flea)): > 15,000 mg/l Exposure time: 21 d

Components:

Biodegradability	: Result: Readily biodegradable. Biodegradation: 71 % Exposure time: 28 d Method: OECD Test Guideline 301B
------------------	---

Biodegradability	: Result: Readily biodegradable. Biodegradation: 80 %
------------------	--

Tire Fitting Lubricant, 5 kg

Version 3.0	Revision Date: 08/10/2018	SDS Number: 1459120-00005	Date of last issue: 04/27/2018 Date of first issue: 02/06/2014
----------------	------------------------------	------------------------------	---

Exposure time: 28 d
Remarks: Based on data from similar materials

Diethylene glycol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 - 80 %
Exposure time: 29 d
Method: OECD Test Guideline 301B

Bioaccumulative potential**Components:****Stearic acid:**

Partition coefficient: n-octanol/water : log Pow: 8.23

Diethylene glycol:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 100

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue:
3.0	08/10/2018	1459120-00005	04/27/2018
			Date of first issue: 02/06/2014

Domestic regulation**TDG**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content	CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products VOC content: 0 % / 0 g/l
---	---

The ingredients of this product are reported in the following inventories:

DSL	: All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
-----	--

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	: Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	: Canada. British Columbia OEL
ACGIH / TWA	: 8-hour, time-weighted average
CA AB OEL / TWA	: 8-hour Occupational exposure limit
CA BC OEL / TWA	: 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-

Tire Fitting Lubricant, 5 kg

Version	Revision Date:	SDS Number:	Date of last issue: 04/27/2018
3.0	08/10/2018	1459120-00005	Date of first issue: 02/06/2014

Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 08/10/2018

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8