

**SELECT SILICONE-FREE ALL PURPOSE
DRESSING VOC COMPLIANT- TIRE
SHINE/DRESSING**

Version	Revision Date:	SDS Number:	Date of last issue: 04/13/2018
1.7	05/06/2018	600000000130	Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : SELECT SILICONE-FREE ALL PURP DRSG 5 GA

Product code : 702261

Manufacturer or supplier's details

Company name of supplier : Niteo Products,LLC

Address : Dallas TX 19162

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200**

Flammable liquids : Category 4

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H227 Combustible liquid.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**
P210 Keep away from heat/sparks/open flames/hot surfaces.
No smoking.

**SELECT SILICONE-FREE ALL PURPOSE
DRESSING VOC COMPLIANT- TIRE
SHINE/DRESSING**

Version 1.7	Revision Date: 05/06/2018	SDS Number: 600000000130	Date of last issue: 04/13/2018 Date of first issue: 05/23/2016
----------------	------------------------------	-----------------------------	---

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

Static-accumulating flammable liquid.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	>= 70 - < 90

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.
If inhaled	: Move to fresh air. Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: If on clothes, remove clothes. If on skin, rinse well with water.

**SELECT SILICONE-FREE ALL PURPOSE
DRESSING VOC COMPLIANT- TIRE
SHINE/DRESSING**

Version	Revision Date:	SDS Number:	Date of last issue: 04/13/2018
1.7	05/06/2018	600000000130	Date of first issue: 05/23/2016

- | | | |
|---|---|--|
| In case of eye contact | : | Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing. |
| If swallowed | : | Obtain medical attention.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician. |
| Most important symptoms and effects, both acute and delayed | : | May be fatal if swallowed and enters airways.
May cause drowsiness or dizziness. |

SECTION 5. FIREFIGHTING MEASURES

- | | | |
|---|---|---|
| Suitable extinguishing media | : | Water spray
Carbon dioxide (CO ₂) |
| Unsuitable extinguishing media | : | High volume water jet |
| Specific hazards during fire-fighting | : | If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release. |
| Hazardous combustion products | : | Carbon oxides |
| Specific extinguishing methods | : | Product is compatible with standard fire-fighting agents. |
| Further information | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use a water spray to cool fully closed containers. |
| Special protective equipment for firefighters | : | In the event of fire, wear self-contained breathing apparatus. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | | |
|---|---|---|
| Personal precautions, protective equipment and emergency procedures | : | Use personal protective equipment.
Remove all sources of ignition.
Ensure adequate ventilation.
Avoid breathing dust.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. |
|---|---|---|

**SELECT SILICONE-FREE ALL PURPOSE
DRESSING VOC COMPLIANT- TIRE
SHINE/DRESSING**

Version 1.7	Revision Date: 05/06/2018	SDS Number: 600000000130	Date of last issue: 04/13/2018 Date of first issue: 05/23/2016
----------------	------------------------------	-----------------------------	---

- Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.
Keep away from open flames, hot surfaces and sources of ignition.
Do not spray on a naked flame or any incandescent material.
- Advice on safe handling : Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Dispose of rinse water in accordance with local and national regulations.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
No smoking.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	TWA (Mist)	5 mg/m3	OSHA Z-1

SAFETY DATA SHEET



SELECT SILICONE-FREE ALL PURPOSE DRESSING VOC COMPLIANT- TIRE SHINE/DRESSING

Version 1.7 Revision Date: 05/06/2018 SDS Number: 600000000130 Date of last issue: 04/13/2018
Date of first issue: 05/23/2016

		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear as appropriate:
Impervious clothing
Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not smoke.
When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : blue green

Odour : like fruit

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : 80 °C

SAFETY DATA SHEET



SELECT SILICONE-FREE ALL PURPOSE DRESSING VOC COMPLIANT- TIRE SHINE/DRESSING

Version	Revision Date:	SDS Number:	Date of last issue: 04/13/2018
1.7	05/06/2018	600000000130	Date of first issue: 05/23/2016

The value is calculated

Evaporation rate	:	No data available
Flammability (liquids)	:	Static-accumulating flammable liquid.
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Density	:	0.835 g/cm ³ (20 °C)
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Viscosity Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Oxidizing properties	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong oxidizing agents Strong reducing agents
Hazardous decomposition products	:	

**SELECT SILICONE-FREE ALL PURPOSE
DRESSING VOC COMPLIANT- TIRE
SHINE/DRESSING**

Version	Revision Date:	SDS Number:	Date of last issue: 04/13/2018
1.7	05/06/2018	600000000130	Date of first issue: 05/23/2016

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Eye contact
Ingestion

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Components:**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

Result: Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

**SELECT SILICONE-FREE ALL PURPOSE
DRESSING VOC COMPLIANT- TIRE
SHINE/DRESSING**

Version 1.7	Revision Date: 05/06/2018	SDS Number: 600000000130	Date of last issue: 04/13/2018 Date of first issue: 05/23/2016
----------------	------------------------------	-----------------------------	---

STOT - single exposure

May cause drowsiness or dizziness.

Components:**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May be fatal if swallowed and enters airways.

Components:**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

May be fatal if swallowed and enters airways.

Further information**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12. ECOLOGICAL INFORMATION

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues	:	Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**SELECT SILICONE-FREE ALL PURPOSE
DRESSING VOC COMPLIANT- TIRE
SHINE/DRESSING**

Version	Revision Date:	SDS Number:	Date of last issue: 04/13/2018
1.7	05/06/2018	600000000130	Date of first issue: 05/23/2016

International Regulations**IATA-DGR**

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

Not regulated as a dangerous good

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
MERCURY	7439-97-6	1	1 (U151)
MERCURY	7439-97-6	1	1 (D009)
LEAD	7439-92-1	10	10 (D008)
ETHYL ACETATE	141-78-6	5000	5000 (U112)
ISOAMYL ACETATE	123-92-2	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Hazard not otherwise classified (physical hazards)
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SAFETY DATA SHEET



SELECT SILICONE-FREE ALL PURPOSE DRESSING VOC COMPLIANT- TIRE SHINE/DRESSING

Version 1.7	Revision Date: 05/06/2018	SDS Number: 600000000130	Date of last issue: 04/13/2018 Date of first issue: 05/23/2016
----------------	------------------------------	-----------------------------	---

US State Regulations

California Prop. 65


WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

WARNING! This product contains a chemical known to the State of California to cause cancer.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Revision Date : 05/06/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN