

SAFETY DATA SHEET



Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2017
1.3	05/02/2018	600000000702	Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : SLEEK WAX 12/32 FOZ

Product code : CBOOA039-02

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : Dallas TX 19162

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Recommended use of the chemical and restrictions on use

Recommended use : WAX

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitisation : Category 1

Carcinogenicity : Category 2

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H351 Suspected of causing cancer.

Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2017
1.3	05/02/2018	600000000702	Date of first issue: 05/23/2016

Precautionary statements

: **Prevention:**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

Static-accumulating flammable liquid.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
NAPHTHA (PETROLEUM),	64742-49-0	>= 10 - < 20

SAFETY DATA SHEET



Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version 1.3 Revision Date: 05/02/2018 SDS Number: 600000000702 Date of last issue: 05/15/2017
Date of first issue: 05/23/2016

HYDROTREATED LIGHT		
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	$\geq 5 - < 10$
MORPHOLINE	110-91-8	$\geq 1 - < 3$
CARBON BLACK	1333-86-4	$\geq 0.1 - < 1$
HEXAHYDRO-1,3,5-TRIS-(-2- HYDROXYETHYL)-S-TRIAZINE	4719-04-4	$\geq 0.1 - < 1$

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Move to fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on clothes, remove clothes.
Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
If skin irritation persists, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Suspected of causing cancer.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Carbon dioxide (CO₂)
Dry chemical
Alcohol-resistant foam
- Unsuitable extinguishing media : High volume water jet

Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2017
1.3	05/02/2018	600000000702	Date of first issue: 05/23/2016

- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
Silicon oxides
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Ensure adequate ventilation.
Avoid breathing dust.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Evacuate personnel to safe areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.
Keep away from open flames, hot surfaces and sources of ignition.

SAFETY DATA SHEET



Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version 1.3 Revision Date: 05/02/2018 SDS Number: 600000000702 Date of last issue: 05/15/2017
Date of first issue: 05/23/2016

- Use only explosion-proof equipment.
Do not spray on a naked flame or any incandescent material.
- Advice on safe handling : Open drum carefully as content may be under pressure.
Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Take precautionary measures against static discharges.
Avoid contact with skin and eyes.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Dispose of rinse water in accordance with local and national regulations.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
No smoking.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
MORPHOLINE	110-91-8	TWA	20 ppm	ACGIH
		TWA	20 ppm 70 mg/m3	NIOSH REL
		ST	30 ppm 105 mg/m3	NIOSH REL
		TWA	20 ppm 70 mg/m3	OSHA Z-1
		TWA	20 ppm	OSHA P0

SAFETY DATA SHEET



Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version 1.3 Revision Date: 05/02/2018 SDS Number: 600000000702 Date of last issue: 05/15/2017
Date of first issue: 05/23/2016

			70 mg/m3	
		STEL	30 ppm 105 mg/m3	OSHA P0
CARBON BLACK	1333-86-4	TWA (Inhalable fraction)	3 mg/m3	ACGIH
		TWA	3.5 mg/m3	NIOSH REL
		TWA	3.5 mg/m3	OSHA Z-1
		TWA	3.5 mg/m3	OSHA P0

Hazardous components without workplace control parameters

Components	CAS-No.
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT	64742-49-0
HEXAHYDRO-1,3,5-TRIS-(-2-HYDROXYETHYL)-S-TRIAZINE	4719-04-4

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear as appropriate:
Impervious clothing
Flame-resistant clothing
Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not smoke.
When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : black

SAFETY DATA SHEET



Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2017
1.3	05/02/2018	600000000702	Date of first issue: 05/23/2016

Odour	:	solvent-like
pH	:	No data available
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	> 150 °F (1013.25 hPa)
Flash point	:	51.1 °C Method: closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Flammability (liquids)	:	Static-accumulating flammable liquid.
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Density	:	ca. 0.954 g/cm ³ (20 °C)
Solubility(ies)	:	
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	2357 mm ² /s (40 °C)
Oxidizing properties	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.

Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2017
1.3	05/02/2018	600000000702	Date of first issue: 05/23/2016

Incompatible materials	:	Acids acrylates Alcohols Aldehydes Bases halogens glycols Halogenated compounds Iron isocyanates Ketones Metals Nitrous acid and other nitrosating agents organic anhydrides Reducing agents Strong oxidizing agents
Hazardous decomposition products	:	Carbon oxides Silicon oxides

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Eye contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: 30.41 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method

Components:**MORPHOLINE:**

Acute oral toxicity	:	LD50 (Rat): ca. 1,900 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	Assessment: The component/mixture is toxic after short term inhalation.

SAFETY DATA SHEET



Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2017
1.3	05/02/2018	600000000702	Date of first issue: 05/23/2016

Acute dermal toxicity : LD50 (Rabbit): ca. 500 mg/kg

CARBON BLACK:

Acute oral toxicity : LD50 (Rat): 8,000 mg/kg

HEXAHYDRO-1,3,5-TRIS-(-2-HYDROXYETHYL)-S-TRIAZINE:

Acute oral toxicity : LD50 (Rat, female): 1,956 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.371 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2 g/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation and/or dermatitis.

Components:

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT:

Result: Possibly irritating to skin

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Result: Repeated exposure may cause skin dryness or cracking.

MORPHOLINE:

Result: Corrosive after 3 minutes or less of exposure

CARBON BLACK:

Species: Rabbit

Result: No skin irritation

HEXAHYDRO-1,3,5-TRIS-(-2-HYDROXYETHYL)-S-TRIAZINE:

Result: Possibly irritating to skin

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2017
1.3	05/02/2018	600000000702	Date of first issue: 05/23/2016

Components:**NAPHTHA (PETROLEUM), HYDROTREATED LIGHT:**

Result: Possibly irritating to eyes

MORPHOLINE:

Result: Irreversible effects on the eye

CARBON BLACK:

Species: Rabbit

Result: No eye irritation

HEXAHYDRO-1,3,5-TRIS-(-2-HYDROXYETHYL)-S-TRIAZINE:

Result: Irreversible effects on the eye

Respiratory or skin sensitisation**Skin sensitisation**

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks: May cause allergic skin reaction.

Components:**CARBON BLACK:**

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

HEXAHYDRO-1,3,5-TRIS-(-2-HYDROXYETHYL)-S-TRIAZINE:

Species: Guinea pig

Assessment: May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Components:**MORPHOLINE:**

Genotoxicity in vitro

: Test Type: unscheduled DNA synthesis assay
Test system: rat hepatocytes
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 482
Result: negative

Test Type: In vitro mammalian cell gene mutation test

Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2017
1.3	05/02/2018	600000000702	Date of first issue: 05/23/2016

Test system: mouse lymphoma cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: positive

CARBON BLACK:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Suspected of causing cancer.

Components:**CARBON BLACK:**

Application Route: Inhalation
Result: positive

IARC

Group 2B: Possibly carcinogenic to humans

CARBON BLACK 1333-86-4

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

Components:**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

Target Organs: Central nervous system
Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

SAFETY DATA SHEET



Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2017
1.3	05/02/2018	600000000702	Date of first issue: 05/23/2016

Components:

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT:

May be fatal if swallowed and enters airways.

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- | | | |
|------------------------|---|--|
| Waste from residues | : | Dispose of in accordance with all applicable local, state and federal regulations. |
| Contaminated packaging | : | Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum. |

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

- | | | |
|--|---|---|
| UN/ID No. | : | UN 1993 |
| Proper shipping name | : | Flammable liquid, n.o.s.
(ALIPHATIC PETROLEUM NAPHTHA) |
| Class | : | 3 |
| Packing group | : | III |
| Labels | : | 3 |
| Packing instruction (cargo aircraft) | : | 366 |
| Packing instruction (passenger aircraft) | : | 355 |

IMDG-Code

- | | | |
|----------------------|---|--------------------------|
| UN number | : | UN 1993 |
| Proper shipping name | : | FLAMMABLE LIQUID, N.O.S. |

SAFETY DATA SHEET



Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version 1.3 Revision Date: 05/02/2018 SDS Number: 600000000702 Date of last issue: 05/15/2017
Date of first issue: 05/23/2016

(ALIPHATIC PETROLEUM NAPHTHA)
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 1993
Proper shipping name : Flammable liquids, n.o.s.
(ALIPHATIC PETROLEUM NAPHTHA)
Class : 3
Packing group : III
Labels : 3
ERG Code : 128
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
TOLUENE	108-88-3	1000	1000 (U220)
XYLENE	1330-20-7	100	100 (F003)
BENZENE	71-43-2	10	10 (U019)
NAPHTHALENE	91-20-3	100	100 (U165)
XYLENE	1330-20-7	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
SULFURIC ACID	7664-93-9	1000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Hazard not otherwise classified (physical hazards)
Skin corrosion or irritation
Serious eye damage or eye irritation
Respiratory or skin sensitisation
Carcinogenicity

SAFETY DATA SHEET



Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2017
1.3	05/02/2018	600000000702	Date of first issue: 05/23/2016

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations


California Prop. 65

WARNING! This product contains a chemical known to the State of California to cause cancer.
WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Revision Date : 05/02/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN