

# True Brand Fuel System Decarbonizer

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations  
Revision Date: 08/31/2015 Date of issue: 08/31/2015

Version: 1.0

### SECTION 1: IDENTIFICATION

#### 1.1. Product Identifier

Product Form: Mixture

Product Name: True Brand Fuel System Decarbonizer

Product Part #: T2100

#### 1.2. Intended Use of the Product

Use of the substance/mixture: Automotive

#### 1.3. Name, Address, and Telephone of the Responsible Party

##### Company

Solid Start, Inc.  
3705 HWY 98 South  
Lakeland, FL 33812  
863-937-9297  
[www.solidstart.biz](http://www.solidstart.biz)

#### 1.4. Emergency Telephone Number

Emergency Number : 813-248-0585 ChemTel

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the Substance or Mixture

##### Classification (GHS-US)

|                   |      |
|-------------------|------|
| Flam. Liq. 2      | H225 |
| Skin Irrit. 2     | H315 |
| Eye Irrit. 2A     | H319 |
| Carc. 2           | H351 |
| Repr. 1B          | H360 |
| STOT SE 3         | H336 |
| STOT RE 2         | H373 |
| Asp. Tox. 1       | H304 |
| Aquatic Chronic 2 | H411 |

Full text of H-phrases: see section 16

#### 2.2. Label Elements

##### GHS-US Labeling

##### Hazard Pictograms (GHS-US)



##### Signal Word (GHS-US)

: Danger

##### Hazard Statements (GHS-US)

: H225 - Highly flammable liquid and vapor.  
H304 - May be fatal if swallowed and enters airways.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.  
H351 - Suspected of causing cancer.  
H360 - May damage fertility or the unborn child.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H411 - Toxic to aquatic life with long lasting effects.

##### Precautionary Statements (GHS-US)

: P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from extremely high or low temperatures, ignition sources, and incompatible materials. - No smoking.  
P240 - Ground/bond container and receiving equipment.  
P241 - Use explosion-proof electrical, ventilating, and lighting equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P260 - Do not breathe vapors, mist, or spray.

# True Brand Fuel System Decarbonizer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, and eye protection.  
P301+P310 - If swallowed: Immediately call a poison center or doctor.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P331 - Do NOT induce vomiting.  
P362 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.  
P391 - Collect spillage.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.  
P403+P233+P235 - Store in a well-ventilated place. Keep container tightly closed. Keep cool.

### 2.3. Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

| Name                                        | Product Identifier  | %       | Classification (GHS-US)                                                                                                                                                      |
|---------------------------------------------|---------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Solvent naphtha, petroleum, light aliphatic | (CAS No) 64742-89-8 | 50 - 60 | Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>STOT SE 3, H336<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401<br>Aquatic Chronic 2, H411                                        |
| Xylenes (o-, m-, p- isomers)                | (CAS No) 1330-20-7  | 30 - 40 | Flam. Liq. 3, H226<br>Acute Tox. 4 (Dermal), H312<br>Acute Tox. 4<br>(Inhalation:vapour), H332<br>Skin Irrit. 2, H315<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401          |
| Ethylbenzene                                | (CAS No) 100-41-4   | 10 - 15 | Flam. Liq. 2, H225<br>Acute Tox. 4<br>(Inhalation:vapour), H332<br>Carc. 2, H351<br>STOT RE 2, H373<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401<br>Aquatic Chronic 3, H412 |
| 1-Methyl-2-pyrrolidone                      | (CAS No) 872-50-4   | 5 - 10  | Flam. Liq. 4, H227<br>Skin Irrit. 2, H315<br>Eye Irrit. 2A, H319<br>Repr. 1B, H360<br>STOT SE 3, H335                                                                        |

# True Brand Fuel System Decarbonizer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                 |                   |        |                                                                                                                                                                           |
|-----------------|-------------------|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2-Butoxyethanol | (CAS No) 111-76-2 | 5 - 10 | Flam. Liq. 4, H227<br>Acute Tox. 4 (Oral), H302<br>Acute Tox. 4 (Dermal), H312<br>Acute Tox. 4<br>(Inhalation:vapour), H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2A, H319 |
|-----------------|-------------------|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

\*The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret.

Full text of H-phrases: see section 16

### SECTION 4: FIRST AID MEASURES

#### 4.1. Description of First Aid Measures

**First-aid Measures General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**First-aid Measures After Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**First-aid Measures After Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

**First-aid Measures After Eye Contact:** Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

**First-aid Measures After Ingestion:** Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms/Injuries:** Causes serious eye irritation. Causes skin irritation. May cause drowsiness and dizziness. Suspected of causing cancer. May damage fertility. May damage the unborn child. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

**Symptoms/Injuries After Inhalation:** High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

**Symptoms/Injuries After Skin Contact:** Redness, pain, swelling, itching, burning, dryness, and dermatitis.

**Symptoms/Injuries After Eye Contact:** Contact causes severe irritation with redness and swelling of the conjunctiva.

**Symptoms/Injuries After Ingestion:** Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

**Chronic Symptoms:** Suspected of causing cancer. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

#### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

### SECTION 5: FIRE-FIGHTING MEASURES

#### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>). Water may be ineffective but water should be used to keep fire-exposed container cool.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. A heavy water stream may spread burning liquid.

#### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Highly flammable liquid and vapor.

**Explosion Hazard:** May form flammable or explosive vapor-air mixture.

**Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion.

#### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Other Information:** Do not allow run-off from fire fighting to enter drains or water courses.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not get in eyes, on skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges. Do not breathe vapor, mist or spray.

##### 6.1.1. For Non-emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel. Stop leak if safe to do so.

# True Brand Fuel System Decarbonizer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.1.2. For Emergency Responders

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Stop leak if safe to do so. Ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Eliminate ignition sources.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Collect spillage.

### 6.3. Methods and Material for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools.

### 6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. See Section 13, Disposal Considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** Handle empty containers with care because residual vapors are flammable.

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid contact with eyes, skin and clothing. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

**Storage Conditions:** Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place.

**Incompatible Products:** Strong acids, strong bases, strong oxidizers.

### 7.3. Specific End Use(s)

Automotive

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), or OSHA (PEL).

| Xylenes (o-, m-, p- isomers) (1330-20-7) |                                       |                                                              |
|------------------------------------------|---------------------------------------|--------------------------------------------------------------|
| USA ACGIH                                | ACGIH TWA (ppm)                       | 100 ppm                                                      |
| USA ACGIH                                | ACGIH STEL (ppm)                      | 150 ppm                                                      |
| USA ACGIH                                | ACGIH chemical category               | Not Classifiable as a Human Carcinogen                       |
| USA OSHA                                 | OSHA PEL (TWA) (mg/m <sup>3</sup> )   | 435 mg/m <sup>3</sup>                                        |
| USA OSHA                                 | OSHA PEL (TWA) (ppm)                  | 100 ppm                                                      |
| Ethylbenzene (100-41-4)                  |                                       |                                                              |
| USA ACGIH                                | ACGIH TWA (ppm)                       | 20 ppm                                                       |
| USA ACGIH                                | ACGIH chemical category               | Confirmed Animal Carcinogen with Unknown Relevance to Humans |
| USA NIOSH                                | NIOSH REL (TWA) (mg/m <sup>3</sup> )  | 435 mg/m <sup>3</sup>                                        |
| USA NIOSH                                | NIOSH REL (TWA) (ppm)                 | 100 ppm                                                      |
| USA NIOSH                                | NIOSH REL (STEL) (mg/m <sup>3</sup> ) | 545 mg/m <sup>3</sup>                                        |
| USA NIOSH                                | NIOSH REL (STEL) (ppm)                | 125 ppm                                                      |
| USA IDLH                                 | US IDLH (ppm)                         | 800 ppm (10% LEL)                                            |
| USA OSHA                                 | OSHA PEL (TWA) (mg/m <sup>3</sup> )   | 435 mg/m <sup>3</sup>                                        |
| USA OSHA                                 | OSHA PEL (TWA) (ppm)                  | 100 ppm                                                      |
| 2-Butoxyethanol (111-76-2)               |                                       |                                                              |
| USA ACGIH                                | ACGIH TWA (ppm)                       | 20 ppm                                                       |
| USA ACGIH                                | ACGIH chemical category               | Confirmed Animal Carcinogen with Unknown Relevance to Humans |
| USA NIOSH                                | NIOSH REL (TWA) (mg/m <sup>3</sup> )  | 24 mg/m <sup>3</sup>                                         |

# True Brand Fuel System Decarbonizer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|           |                                     |                                   |
|-----------|-------------------------------------|-----------------------------------|
| USA NIOSH | NIOSH REL (TWA) (ppm)               | 5 ppm                             |
| USA IDLH  | US IDLH (ppm)                       | 700 ppm                           |
| USA OSHA  | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 240 mg/m <sup>3</sup>             |
| USA OSHA  | OSHA PEL (TWA) (ppm)                | 50 ppm                            |
| USA OSHA  | Limit value category (OSHA)         | prevent or reduce skin absorption |


### 8.2. Exposure Controls

#### Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment.

#### Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



#### Materials for Protective Clothing

: Chemically resistant materials and fabrics. Wear fire/flamm resistant/retardant clothing.

#### Hand Protection

: Wear protective gloves.

#### Eye Protection

: Chemical safety goggles.

#### Skin and Body Protection

: Wear suitable protective clothing.

#### Respiratory Protection

: In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

#### Other Information

: When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

|                                        |                     |
|----------------------------------------|---------------------|
| Physical State                         | : Liquid            |
| Appearance                             | : Clear             |
| Odor                                   | : No data available |
| Odor Threshold                         | : No data available |
| pH                                     | : No data available |
| Evaporation Rate                       | : No data available |
| Melting Point                          | : No data available |
| Freezing Point                         | : No data available |
| Boiling Point                          | : No data available |
| Flash Point                            | : 10 °C (50 °F)     |
| Auto-ignition Temperature              | : No data available |
| Decomposition Temperature              | : No data available |
| Flammability (solid, gas)              | : No data available |
| Vapor Pressure                         | : No data available |
| Relative Vapor Density at 20 °C        | : No data available |
| Relative Density                       | : No data available |
| Solubility                             | : No data available |
| Partition Coefficient: N-Octanol/Water | : No data available |
| Viscosity                              | : No data available |

### 9.2. Other Information: No additional information available

## SECTION 10: STABILITY AND REACTIVITY

10.1. **Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion.

10.2. **Chemical Stability:** Extremely flammable liquid and vapor. May form flammable or explosive vapor-air mixture.

10.3. **Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

# True Brand Fuel System Decarbonizer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**10.4. Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

**10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.

**10.6. Hazardous Decomposition Products:** Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on Toxicological Effects

Acute Toxicity: Not classified

|                                                                 |                                       |
|-----------------------------------------------------------------|---------------------------------------|
| <b>Solvent naphtha, petroleum, light aliphatic (64742-89-8)</b> |                                       |
| LD50 Oral Rat                                                   | > 5000 mg/kg                          |
| LD50 Dermal Rabbit                                              | 3000 mg/kg                            |
| <b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>                 |                                       |
| LD50 Oral Rat                                                   | > 5000 mg/kg                          |
| LD50 Dermal Rabbit                                              | > 4350 mg/kg                          |
| LC50 Inhalation Rat                                             | 29.08 mg/l/4h                         |
| LC50 Inhalation Rat                                             | 6247 ppm/4h (species: Sprague-Dawley) |
| <b>Ethylbenzene (100-41-4)</b>                                  |                                       |
| LD50 Oral Rat                                                   | 3500 mg/kg                            |
| LD50 Dermal Rabbit                                              | 15400 mg/kg                           |
| LC50 Inhalation Rat                                             | 17.2 mg/l/4h (Exposure time: 4 h)     |
| <b>1-Methyl-2-pyrrolidone (872-50-4)</b>                        |                                       |
| LD50 Oral Rat                                                   | 4150 mg/kg                            |
| LD50 Dermal Rabbit                                              | > 5000 mg/kg                          |
| LC50 Inhalation Rat                                             | 5.1 mg/l/4h                           |
| <b>2-Butoxyethanol (111-76-2)</b>                               |                                       |
| LD50 Oral Rat                                                   | 470 mg/kg                             |
| LC50 Inhalation Rat                                             | 450 ppm/4h                            |

**Skin Corrosion/Irritation:** Causes skin irritation.

**Serious Eye Damage/Irritation:** Causes serious eye irritation.

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** Not classified

**Carcinogenicity:** Suspected of causing cancer.

|                                                 |                                               |
|-------------------------------------------------|-----------------------------------------------|
| <b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b> |                                               |
| IARC group                                      | 3                                             |
| <b>Ethylbenzene (100-41-4)</b>                  |                                               |
| IARC group                                      | 2B                                            |
| National Toxicology Program (NTP) Status        | Evidence of Carcinogenicity.                  |
| OSHA Hazard Communication Carcinogen List       | In OSHA Hazard Communication Carcinogen list. |
| <b>2-Butoxyethanol (111-76-2)</b>               |                                               |
| IARC group                                      | 3                                             |

**Reproductive Toxicity:** May damage fertility or the unborn child.

**Specific Target Organ Toxicity (Single Exposure):** May cause drowsiness or dizziness.

**Specific Target Organ Toxicity (Repeated Exposure):** May cause damage to organs through prolonged or repeated exposure.

**Aspiration Hazard:** May be fatal if swallowed and enters airways.

**Symptoms/Injuries After Inhalation:** High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

**Symptoms/Injuries After Skin Contact:** Redness, pain, swelling, itching, burning, dryness, and dermatitis.

**Symptoms/Injuries After Eye Contact:** Contact causes severe irritation with redness and swelling of the conjunctiva.

**Symptoms/Injuries After Ingestion:** Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

**Chronic Symptoms:** Suspected of causing cancer. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

**Ecology - General** : Toxic to aquatic life with long lasting effects.

# True Brand Fuel System Decarbonizer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                                                 |                                                                                          |
|-------------------------------------------------|------------------------------------------------------------------------------------------|
| <b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b> |                                                                                          |
| LC50 Fish 1                                     | 3.3 mg/l                                                                                 |
| EC50 Daphnia 1                                  | 3.82 mg/l (Exposure time: 48 h - Species: water flea)                                    |
| LC 50 Fish 2                                    | 2.661 (2.661 - 4.093) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static]) |
| NOEC chronic crustacea                          | 1.17                                                                                     |
| <b>Ethylbenzene (100-41-4)</b>                  |                                                                                          |
| LC50 Fish 1                                     | 11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])           |
| EC50 Daphnia 1                                  | 1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)                            |
| LC 50 Fish 2                                    | 4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])              |
| <b>1-Methyl-2-pyrrolidone (872-50-4)</b>        |                                                                                          |
| LC50 Fish 1                                     | 832 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])                   |
| EC50 Daphnia 1                                  | 4897 mg/l (Exposure time: 48 h - Species: Daphnia magna)                                 |
| LC 50 Fish 2                                    | 1072 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])                  |
| <b>2-Butoxyethanol (111-76-2)</b>               |                                                                                          |
| LC50 Fish 1                                     | 1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])                  |
| EC50 Daphnia 1                                  | 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)                                 |
| LC 50 Fish 2                                    | 2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)                           |

### 12.2. Persistence and Degradability

|                                            |                                                         |
|--------------------------------------------|---------------------------------------------------------|
| <b>True Brand Fuel System Decarbonizer</b> |                                                         |
| Persistence and Degradability              | May cause long-term adverse effects in the environment. |

### 12.3. Bioaccumulative Potential

|                                                 |                  |
|-------------------------------------------------|------------------|
| <b>True Brand Fuel System Decarbonizer</b>      |                  |
| Bioaccumulative Potential                       | Not established. |
| <b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b> |                  |
| BCF fish 1                                      | 0.6 (0.6 - 15)   |
| Log Pow                                         | 2.77 - 3.15      |
| <b>Ethylbenzene (100-41-4)</b>                  |                  |
| BCF fish 1                                      | 15               |
| Log Pow                                         | 3.118            |
| <b>1-Methyl-2-pyrrolidone (872-50-4)</b>        |                  |
| Log Pow                                         | -0.46 (at 25 °C) |
| <b>2-Butoxyethanol (111-76-2)</b>               |                  |
| Log Pow                                         | 0.81 (at 25 °C)  |

### 12.4. Mobility in Soil: No additional information available

### 12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, and international regulations.

**Additional Information:** Handle empty containers with care because residual vapors are flammable.

**Ecology – Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

## SECTION 14: TRANSPORT INFORMATION

### 14.1. In Accordance with DOT

Proper Shipping Name : PETROLEUM DISTILLATES, N.O.S.

Hazard Class : 3  
Identification Number : UN1268  
Label Codes : 3  
Packing Group : II



### 14.2. In Accordance with IMDG

# True Brand Fuel System Decarbonizer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name : PETROLEUM DISTILLATES, N.O.S.  
Hazard Class : 3  
Identification Number : UN1268  
Packing Group : II  
Label Codes : 3  
EmS-No. (Fire) : F-E  
EmS-No. (Spillage) : S-E



### 14.3. In Accordance with IATA

Proper Shipping Name : PETROLEUM DISTILLATES, N.O.S.  
Packing Group : II  
Identification Number : UN1268  
Hazard Class : 3  
Label Codes : 3  
ERG Code (IATA) : 3H



## SECTION 15: REGULATORY INFORMATION

### 15.1 US Federal Regulations

|                                                                           |                                                                                        |
|---------------------------------------------------------------------------|----------------------------------------------------------------------------------------|
| True Brand Fuel System Decarbonizer                                       |                                                                                        |
| SARA Section 311/312 Hazard Classes                                       | Fire hazard<br>Immediate (acute) health hazard<br>Delayed (chronic) health hazard      |
| Solvent naphtha, petroleum, light aliphatic (64742-89-8)                  |                                                                                        |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |                                                                                        |
| Xylenes (o-, m-, p- isomers) (1330-20-7)                                  |                                                                                        |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |                                                                                        |
| Listed on United States SARA Section 313                                  |                                                                                        |
| RQ (Reportable quantity, section 304 of EPA's List of Lists)              | 100 lb                                                                                 |
| SARA Section 311/312 Hazard Classes                                       | Delayed (chronic) health hazard<br>Fire hazard<br>Immediate (acute) health hazard      |
| SARA Section 313 - Emission Reporting                                     | 1.0 %                                                                                  |
| Ethylbenzene (100-41-4)                                                   |                                                                                        |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |                                                                                        |
| Listed on United States SARA Section 313                                  |                                                                                        |
| RQ (Reportable quantity, section 304 of EPA's List of Lists)              | 1000 lb                                                                                |
| SARA Section 313 - Emission Reporting                                     | 0.1 %                                                                                  |
| 1-Methyl-2-pyrrolidone (872-50-4)                                         |                                                                                        |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |                                                                                        |
| Listed on United States SARA Section 313                                  |                                                                                        |
| EPA TSCA Regulatory Flag                                                  | T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA. |
| SARA Section 313 - Emission Reporting                                     | 1.0 %                                                                                  |
| 2-Butoxyethanol (111-76-2)                                                |                                                                                        |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |                                                                                        |

### 15.2 US State Regulations

|                                                             |                                                                                                   |
|-------------------------------------------------------------|---------------------------------------------------------------------------------------------------|
| Ethylbenzene (100-41-4)                                     |                                                                                                   |
| U.S. - California - Proposition 65 - Carcinogens List       | WARNING: This product contains chemicals known to the State of California to cause cancer.        |
| 1-Methyl-2-pyrrolidone (872-50-4)                           |                                                                                                   |
| U.S. - California - Proposition 65 - Developmental Toxicity | WARNING: This product contains chemicals known to the State of California to cause birth defects. |
| Xylenes (o-, m-, p- isomers) (1330-20-7)                    |                                                                                                   |

# True Brand Fuel System Decarbonizer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Ethylbenzene (100-41-4)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
U.S. - Pennsylvania - RTK (Right to Know) List

### 1-Methyl-2-pyrrolidone (872-50-4)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### 2-Butoxyethanol (111-76-2)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision Date** : 08/31/2015  
**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

### GHS Full Text Phrases:

|                                  |                                                                  |
|----------------------------------|------------------------------------------------------------------|
| Acute Tox. 4 (Dermal)            | Acute toxicity (dermal) Category 4                               |
| Acute Tox. 4 (Inhalation:vapour) | Acute toxicity (inhalation:vapour) Category 4                    |
| Acute Tox. 4 (Oral)              | Acute toxicity (oral) Category 4                                 |
| Aquatic Acute 2                  | Hazardous to the aquatic environment - Acute Hazard Category 2   |
| Aquatic Chronic 2                | Hazardous to the aquatic environment - Chronic Hazard Category 2 |
| Aquatic Chronic 3                | Hazardous to the aquatic environment - Chronic Hazard Category 3 |
| Asp. Tox. 1                      | Aspiration hazard Category 1                                     |
| Carc. 2                          | Carcinogenicity Category 2                                       |
| Eye Irrit. 2A                    | Serious eye damage/eye irritation Category 2A                    |
| Flam. Liq. 2                     | Flammable liquids Category 2                                     |
| Flam. Liq. 3                     | Flammable liquids Category 3                                     |
| Flam. Liq. 4                     | Flammable liquids Category 4                                     |
| Repr. 1B                         | Reproductive toxicity Category 1B                                |
| Skin Irrit. 2                    | Skin corrosion/irritation Category 2                             |
| STOT RE 2                        | Specific target organ toxicity (repeated exposure) Category 2    |
| STOT SE 3                        | Specific target organ toxicity (single exposure) Category 3      |
| STOT SE 3                        | Specific target organ toxicity (single exposure) Category 3      |
| H225                             | Highly flammable liquid and vapor                                |
| H226                             | Flammable liquid and vapor                                       |
| H227                             | Combustible liquid                                               |
| H302                             | Harmful if swallowed                                             |
| H304                             | May be fatal if swallowed and enters airways                     |
| H312                             | Harmful in contact with skin                                     |
| H315                             | Causes skin irritation                                           |
| H319                             | Causes serious eye irritation                                    |
| H332                             | Harmful if inhaled                                               |
| H335                             | May cause respiratory irritation                                 |
| H336                             | May cause drowsiness or dizziness                                |
| H351                             | Suspected of causing cancer                                      |

# True Brand Fuel System Decarbonizer

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|      |                                                                   |
|------|-------------------------------------------------------------------|
| H360 | May damage fertility or the unborn child                          |
| H373 | May cause damage to organs through prolonged or repeated exposure |
| H401 | Toxic to aquatic life                                             |
| H411 | Toxic to aquatic life with long lasting effects                   |
| H412 | Harmful to aquatic life with long lasting effects                 |

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

SDS US (GHS HazCom)