

SAFETY DATA SHEET



Car Brite™ TROPICAL GLOSS Aerosol Wax

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2018
1.3	05/06/2018	600000000812	Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : TROPICAL GLOSS AERO WAX 15 FOZ 1 UN

Product code : CBO1A069-18

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : Dallas TX 19162

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Recommended use of the chemical and restrictions on use

Recommended use : WAX

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable aerosols : Category 1

Skin irritation : Category 2

Eye irritation : Category 2A

Specific target organ toxicity
- single exposure : Category 3 (Central nervous system)

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Car Brite™ TROPICAL GLOSS Aerosol Wax

Version	Revision Date:	SDS Number:	Date of last issue:
1.3	05/06/2018	600000000812	04/12/2018
			Date of first issue: 05/23/2016

Precautionary statements

: **Prevention:**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
NAPHTHA (PETROLEUM), HEAVY ALKYLATE	64741-65-7	>= 30 - < 50
PROPANE / ISOBUTANE / N-BUTANE	68476-86-8	>= 30 - < 50
KEROSENE	8008-20-6	>= 10 - < 20
ISOPROPANOL	67-63-0	>= 10 - < 20
MINERAL SPIRITS REGULAR	8052-41-3	>= 10 - < 20

Car Brite™ TROPICAL GLOSS Aerosol Wax

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2018
1.3	05/06/2018	600000000812	Date of first issue: 05/23/2016

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

- | | |
|---|---|
| General advice | : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance. |
| If inhaled | : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician. |
| In case of skin contact | : If on clothes, remove clothes.
Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
If skin irritation persists, call a physician. |
| In case of eye contact | : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing. |
| If swallowed | : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician. |
| Most important symptoms and effects, both acute and delayed | : May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness. |

SECTION 5. FIREFIGHTING MEASURES

- | | |
|---------------------------------------|---|
| Suitable extinguishing media | : Water spray
Carbon dioxide (CO ₂)
Dry chemical
Alcohol-resistant foam |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during fire-fighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : Carbon oxides |
| Specific extinguishing methods | : Product is compatible with standard fire-fighting agents. |
| Further information | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must |

Car Brite™ TROPICAL GLOSS Aerosol Wax

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2018
1.3	05/06/2018	600000000812	Date of first issue: 05/23/2016

be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.
for firefighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Ensure adequate ventilation.
Avoid breathing dust.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Evacuate personnel to safe areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Keep away from open flames, hot surfaces and sources of ignition.
Use only explosion-proof equipment.
Do not spray on a naked flame or any incandescent material.

Advice on safe handling : Open drum carefully as content may be under pressure.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not smoke.
Take precautionary measures against static discharges.
Avoid contact with skin and eyes.
Dispose of rinse water in accordance with local and national regulations.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
No smoking.

SAFETY DATA SHEET



Car Brite™ TROPICAL GLOSS Aerosol Wax

Version 1.3 Revision Date: 05/06/2018 SDS Number: 600000000812 Date of last issue: 04/12/2018
Date of first issue: 05/23/2016

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
NAPHTHA (PETROLEUM), HEAVY ALKYLATE	64741-65-7	TWA	500 ppm 2,000 mg/m ³	OSHA Z-1
		TWA	400 ppm 1,600 mg/m ³	OSHA P0
PROPANE / ISOBUTANE / N-BUTANE	68476-86-8	TWA	1,000 ppm 1,800 mg/m ³	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m ³	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m ³	OSHA P0
KEROSENE	8008-20-6	TWA	100 mg/m ³	NIOSH REL
ISOPROPANOL	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m ³	NIOSH REL
		ST	500 ppm 1,225 mg/m ³	NIOSH REL
		TWA	400 ppm 980 mg/m ³	OSHA Z-1
		TWA	400 ppm 980 mg/m ³	OSHA P0
		STEL	500 ppm 1,225 mg/m ³	OSHA P0
MINERAL SPIRITS REGULAR	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m ³	NIOSH REL
		C	1,800 mg/m ³	NIOSH REL
		TWA	500 ppm 2,900 mg/m ³	OSHA Z-1
		TWA	100 ppm 525 mg/m ³	OSHA P0

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
ISOPROPANOL	67-63-0	Acetone	Urine	End of shift at end of work-week	40 mg/l	ACGIH BEI

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

Car Brite™ TROPICAL GLOSS Aerosol Wax

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2018
1.3	05/06/2018	600000000812	Date of first issue: 05/23/2016

apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear as appropriate:
Impervious clothing
Flame-resistant clothing
Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not smoke.
When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: aerosol
Odour	: pleasant
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: 35 °C The value is calculated
Flash point	: -96.4 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Self-ignition	: No data available
Upper explosion limit / Upper flammability limit	: 12.0 %(V)
Lower explosion limit / Lower flammability limit	: 0.6 %(V)
Vapour pressure	: 23.33 hPa (20 °C) The value is calculated

SAFETY DATA SHEET



Car Brite™ TROPICAL GLOSS Aerosol Wax

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2018
1.3	05/06/2018	600000000812	Date of first issue: 05/23/2016

Density	:	0.79 g/cm3
Solubility(ies)	:	
Water solubility	:	practically insoluble
Partition coefficient: n-octanol/water	:	No data available
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	Not applicable
Oxidizing properties	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks. Heat Heat, flames and sparks.
Incompatible materials	:	Strong oxidizing agents strong acids Strong bases
Hazardous decomposition products	:	

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Eye contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity	:	Acute toxicity estimate: 17.5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 5,000 mg/kg

Car Brite™ TROPICAL GLOSS Aerosol Wax

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2018
1.3	05/06/2018	600000000812	Date of first issue: 05/23/2016

Method: Calculation method

Components:**NAPHTHA (PETROLEUM), HEAVY ALKYLATE:**

Acute oral toxicity : LD50 (Rat): > 7,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.04 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

KEROSENE:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 420

Acute inhalation toxicity : LC50 (Rat): > 5.8 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

ISOPROPANOL:

Acute oral toxicity : LD50 (Rat): 5.84 g/kg

Acute inhalation toxicity : LC50 (Rat): 16000 ppm
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12,800 mg/kg

MINERAL SPIRITS REGULAR:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3 g/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May irritate skin.

Car Brite™ TROPICAL GLOSS Aerosol Wax

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2018
1.3	05/06/2018	600000000812	Date of first issue: 05/23/2016

Components:**NAPHTHA (PETROLEUM), HEAVY ALKYLATE:**

Result: Irritating to skin.

PROPANE / ISOBUTANE / N-BUTANE:

Result: Possibly irritating to skin

KEROSENE:

Result: Irritating to skin.

ISOPROPANOL:

Result: Possibly irritating to skin

MINERAL SPIRITS REGULAR:

Result: Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:**PROPANE / ISOBUTANE / N-BUTANE:**

Result: Possibly irritating to eyes

KEROSENE:

Result: Possibly irritating to eyes

ISOPROPANOL:

Result: Irritating to eyes.

MINERAL SPIRITS REGULAR:

Result: Possibly irritating to eyes

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

SAFETY DATA SHEET



Car Brite™ TROPICAL GLOSS Aerosol Wax

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2018
1.3	05/06/2018	600000000812	Date of first issue: 05/23/2016

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

NAPHTHA (PETROLEUM), HEAVY ALKYLATE:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

KEROSENE:

Assessment: May cause drowsiness or dizziness.

ISOPROPANOL:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

NAPHTHA (PETROLEUM), HEAVY ALKYLATE:

May be fatal if swallowed and enters airways.

KEROSENE:

May be fatal if swallowed and enters airways.

MINERAL SPIRITS REGULAR:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

Car Brite™ TROPICAL GLOSS Aerosol Wax

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2018
1.3	05/06/2018	600000000812	Date of first issue: 05/23/2016

SECTION 12. ECOLOGICAL INFORMATION

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues	:	Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations**IATA-DGR**

UN/ID No.	:	UN 1950
Proper shipping name	:	Aerosols, flammable
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	2.1
Packing instruction (cargo aircraft)	:	203
Packing instruction (passenger aircraft)	:	203

IMDG-Code

UN number	:	UN 1950
Proper shipping name	:	AEROSOLS
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	2.1
EmS Code	:	F-D, S-U
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

UN/ID/NA number	:	UN 1950
Proper shipping name	:	Aerosols
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	2.1

SAFETY DATA SHEET



Car Brite™ TROPICAL GLOSS Aerosol Wax

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2018
1.3	05/06/2018	600000000812	Date of first issue: 05/23/2016

ERG Code	:	126
Marine pollutant	:	no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Skin corrosion or irritation
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations


California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Revision Date : 05/06/2018

SAFETY DATA SHEET



Car Brite™ TROPICAL GLOSS Aerosol Wax

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2018
1.3	05/06/2018	600000000812	Date of first issue: 05/23/2016

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN